

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

14-20-0603-10010

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

Navajo Tribe

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

North Hogback 12

9. WELL NO.

9

10. FIELD AND POOL, OR WILDCAT

Slickrock - Dakota

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 12, T29N, R17W

12. COUNTY OR PARISH

San Juan

13. STATE

NM

1.

OIL WELL ☒ GAS WELL ☐ OTHER

2. NAME OF OPERATOR

Walter Duncan

3. ADDRESS OF OPERATOR

Box 234, Farmington, New Mexico 87401

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

2140' FNL - 165' FEL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

5044' GR

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

12-6-74

Ran 23 jts 4-1/2" OD 10.5# 8Rd ST&C "B" Condition casing. TE 724.49' set at 723' ^{GR} ~~RKB~~ cemented by Dowell with 65 sx Class "A" neat, good circulation while cementing, trace cement to surface. Bumped plug with 825 psi. POB 2:30 PM 12-5-74. Left shut in over-night.

12-7-74

Cut off 4-1/2" casing. Welded on 4-1/2" slip-on collar. Picked up 2-3/8" tubing and unloaded water down to top of plug. Dried hole and made 6' new hole to TD of 729'. Approximately 2' with no show and 4' of pay section blowing free oil from hole last 1-1/2' to 2'. Pulled tubing and bit. Reran 23 jts 2-3/8" OD 4.7# 8Rd EUE "B" Condition tubing plus mud anchor, perforating nipple, and seating nipple. TE 716.49' set at 715' ~~RKB~~. Landed tubing and shut well in.

Ge

RECEIVED

DEC 11 1974

U. S. GEOLOGICAL SURVEY

18. I hereby certify that the foregoing is true and correct

SIGNED

Jim L. Jacobs

TITLE

Geologist

DATE

12-10-74

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: