

Form 9-331
(May 1965)UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on reverse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

14-20-0603-9591

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

Navajo

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

North Hogback 1

9. WELL NO.

21

10. FIELD AND POOL, OR WILDCAT

Slickrock Dakota

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 1, T29N, R17W

12. COUNTY OR PARISH

San Juan

13. STATE

NM

SUNDRY NOTICES AND REPORTS ON WELLS
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Walter Duncan

3. ADDRESS OF OPERATOR

Box 234, Farmington, NM 87401

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

2586' FNL - 2380' FWL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

4980' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☒FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☐REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐Completion ☒

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

4-18-75

Moved in Millikin cable tool rig. Drove 7" csg thru boulders to 19' and drilled below csg to 25'. Cemented w/3 sx in btm and 1-1/2 sx around outside.

4-25-75

Ran 19 jts 4-1/2" OD 9.5# KEW 8R ST&C IPSCO new csg. TE 669.25 set at 665' GR. Cemented by Dowell w/75 sx Class "B". Good mud returns while cementing, trace cement to surface. Max cementing press 400 psi. Bumped plug w/1000 psi. POB 8:00 PM, 4-24-75. WOC.

4-26-75

TD 675' with open hole from 665-675'. Laid down bit and ran 21 jts 2-3/8" OD 4.7# 8R EUE "B" condition tbg. TE 656.37 set at 655' GR. Job complete 4:00 PM, 4-25-75.

18. I hereby certify that the foregoing is true and correct

SIGNED

Jim L. Jacobs

TITLE

Geologist

DATE

5-29-75

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side