

MAY 24 1985

BUREAU OF LAND MANAGEMENT
FARMINGTON RESOURCE AREA

Form Approved.
Budget Bureau No. 42-R1424

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ gas ☐ other

2. NAME OF OPERATOR

Raymond T. Duncan

3. ADDRESS OF OPERATOR

1777 S. Harrison St. P-1 Denver. CO 80210

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 2770' FNL & 900' FEL

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,
REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

PULL OR ALTER CASING

MULTIPLE COMPLETE

CHANGE ZONES

ABANDON*

(other)

RECEIVED (NOTE: Report results of multiple completion or zone change on Form 9-130a)
MAY 20 1985
MAY 31 1985

BUREAU OF LAND MANAGEMENT
FARMINGTON RESOURCE AREA

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Subject well to be P&A'd as follows:

1. Pull rods and tubing.
2. Pump 10 sx plug down casing. Displace to bottom of hole - interval 699'-579'.
3. Pump 5 sx plug - interval 60' to surface.
4. Dig down and cut-off casing 4' below ground level.
5. Weld plate on top of casing.
6. Clean and restore location per BLM requirements.

Casing will be cut-off below ground level because well is in cultivated area.
Work would be performed in late fall to minimize impact on crops and land.

18. I hereby certify that the foregoing is true and correct

SIGNED

John A. Bettridge

TITLE Operations Supt.

DATE _____

APPROVED

May 16, 1985

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATA

MAY 29 1985

AREA MANAGER
FARMINGTON RESOURCE AREA

***See Instructions on Reverse Side**

NMOCC