5-USGS I-Dunca	in i—File				/	
Form 9-331 (May 1963)	UNITI DEPARTMENT	ED STATES OF THE INTERIG	SUBMIT IN TRIPLICA (Other instructions of verse side)	ATE Form a Budget 5. LEASE DESIGNA	pproved. Bureau No. 42-R1424. TION AND SERIAL NO.	
		GICAL SURVEY		14-20-06	03-9591	
		AND REPORTS C	N WELLS ck to a different reservoir. oposals.)	6. IF INDIAN, ALL	ribe	
OIL GAS WELL	OTHER			7. UNIT AGREEME		
2. NAME OF OPERATOR				8. FARM OR LEAS	E NAME	
Walter D	ouncan		COLLINE	North Ho	gback I	
3. ADDRESS OF OPERATOR			RELEIVED	9. WELL NO.		
4. LOCATION OF WELL (R	eport location clearly an	lew Mexico 8740 d in accordance with any S			OL, OB WILDCAT	
See also space 17 belo At surface	w.)		APR 21 1975	Slickron	k - Dakota	
2450° FSL 1520° FEL			1	/ 11 pro m p w	11. SEC., T., E., M., OR BLK. AND SURVEY OR AREA	
			OIL CON. COM			
14. PERMIT NO.	15 E	EVATIONS (Show whether DF.		Sec. ,	T29N, RITW	
II. IBRAIL NO.	10. 52	4986 GR	, diq co,	San Juan		
16.	Check Approprie	• • • • • • • • • • • • • • • • • • • •	ature of Notice, Report,			
NOTICE OF INTENTION TO: SUBSEQU						
TEST WATER SHUT-OF	PULL OR	ALTER CASING	WATER SHUT-OFF	Y REPAIR	ING WELL	
FRACTURE TREAT	[]	COMPLETE	FRACTURE TREATMENT		NG CASING	
SHOOT OR ACIDIZE	ABANDON	•	SHOOTING OR ACIDIZING	ABANDO	NMENT*	
REPAIR WELL	CHANGE 1	PLANS	(Other)			
(Other)			(Note: Report re Completion or Re	esults of multiple comple completion Report and L	ction on Well og form.)	
17. DESCRIBE PROPOSED OR proposed work. If nent to this work.)	well is directionally dri	(Clearly state all pertinent lled, give subsurface locati	details, and give pertinent on and measured and true v	dates, including estimate vertical destriction and market and mark	d date of starting any arkers and zones perti-	
	illiken cable 1 1 csg w/5 sx.	tool rig and dro	ve 7" csg to 25".	Dri 13 ed 10' 1	pelow 7"	
logger's TD set at 662' Max cementi	662. Ran 22 GR, cemented v	jts 4-1/2" OD 10 v/75 sx Class "A si, bumped plug	ipe. Ran ES log 0.5# 8R ST&C "B" " neat, good mud w/800 psi, trace	condition csg. returns while o	TE 674.00 cementing.	
Leii Saut i	1. 100 2.50 11	ng 4-11-751	•			
bit. Blew l Drilled 8 c from hole la TE 648.73 se	nole down with open hole (fire ast 2-1/2"). f	air, drilled plost 5 no show, led bit and relationship.	ple. Picked up 2 ug and guide shoe ast 3º good odor an 2! jts 2-3/8º open hole 662-670	, and dried up and blowing fro OD 4.7# 8R EUE	hole. ee oil tbg.	
18. I hereby certify that	the/foregoing is true an	d correct	Engineer	DATE	4-16-75	
(This space for Feder	Mas A. Dugan/ ral or State office use)			مدير ر		
APPROVED BY	V	TITLE		APR 1 8 15	APR 1 8 1975	