Form	9-331
(May	1963)

UNITED STATES SUBMIT IN TRIPLICATE* DEPARTMENT OF THE INTERIOR (Other instructions on reverse side)

Form approved Budget Bureay No. 42-R1424. 5. LEASE DESIGNATION AND SERIAL NO. NM-012711

GFO!	OGICAL	SURVEY	

SUNDRY	NOTICES	AND	REPORTS	ON	WFLIS
JULTURI	1101165	\sim 110	IVEL OILLS	\sim 11	TTLLLJ

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

TT, TURNITA NO.	6189'	San Juan New Mexico	
14. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT, GR, etc.)	Sec. 3, T30N, R8W	
815' FSL and 110	11. SEC., T., R., M., OR BLE. AND SURVEY OR AREA		
4. LOCATION OF WELL (Report See also space 17 below.) At surface	10. FIELD AND POOL, OR WILDCAT Blanco Mesa Verde		
3. ADDRESS OF OPERATOR 1860 Lincoln St.	9. WELL NO. 36A		
2. NAME OF OPERATOR Tenneco Oil Comp	8. FABM OR LEASE NAME Florance		
1. OIL GAS X WELL WELL X	7. UNIT AGREEMENT NAME		
(Do not use this form Use			

NOTICE OF INTENTION TO:				SUBSEQUENT REPORT OF:		
TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL		PULL OR ALTER CASING MULTIPLE COMPLETE ABANDON* CHANGE PLANS		WATER SHUT-OFF FRACTURE TREATMENT SHOOTING OR ACIDIZING (Other) (Note: Report results of multiple completion on Well		
(Other)			<u> </u>	(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)		

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

6/23/75- 7/31/75 Waiting on completion

8/1 Going in hole with 2 3/8" tubing. MIRUPU. Loaded casing with water, pumped at 1900 psi, ½ barrel per minute. Ran 80 joints of 2 3/8" tubing. Shut down over night. 8/2/75 Finished goin in hole and tagged PBTB of 5632 with 178 joints of 2 3/8" tubing. POH, Ran and set packer at 3085', tested 4½" casing below packer. Held OK. 8/3/75 Went in hole with 7" packer. Tagged liner top at 3046'. Set packer at 3024'. Pumped in below packer. Squeezed liner with 50 sacks Class B cement to 4500 psi. Squeeze press.

8/4/75 Pulled out of hole with tubing and bit. Went in hole with 6 3/4" bit, cleaned out cement to top of liner.



18. I hereby certify that the foregoing is true and correct SIGNED	Production Clerk	DATE 8/5/75
(This space for Federal or State office use)		
APPROVED BYCONDITIONS OF APPROVAL, IF ANY:	TITLE	DATE