

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well ☐ gas ☒ well ☐ other

2. NAME OF OPERATOR  
El Paso Natural Gas Company

3. ADDRESS OF OPERATOR  
P.O. Box 289, Farmington, New Mexico 84701

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 1810'N, 1095'W  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:		SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF	<input type="checkbox"/>	<input checked="" type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>	<input checked="" type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>	<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>	<input type="checkbox"/>
(other)		

5. LEASE  
SF 078596

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME  
Howell C.

9. WELL NO.  
4A

10. FIELD OR WILDCAT NAME  
Blanco M.V.

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec. 18, T-30-N, R-8-W  
N.M.P.M.

12. COUNTY OR PARISH  
San Juan

13. STATE  
New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
6293' GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

12-27-78: TD 3491'. Ran 89 jts. 7", 20#, KS intermediate casing, 3475' set at 3491'. Cemented w/376 cu. ft. cement. WOC 12 hours; held 1200#/30 minutes. Top of cement at 1825'.

12-31-78: TD 5720'. Ran 76 jts. 4 1/2", 10.5#, K-55 casing liner, 2393' set 3327-5720'. Float collar set at 5703'. Cemented w/415 cu. ft. cement. WOG 18 hours.

3-19-79: PBTD 5703'. Tested casing to 3500#, OK. Perfed 5084, 5120, 5128, 5134, 5239, 5245, 5284, 5291, 5298, 5305, 5312, 5319, 5326, 5334, 5343, 5350, 5372, 5402, 5414, 5506, 5534, 5553, 5610, 5638, 5644, 5650, 5668' w/1 SPZ. Fraced w/81,000# 20/40 sand and 162,000 gal. water. Flushed w/6750 gal. water. Perfed 4576, 4654, 4698, 4724, 4790, 4796, 4802, 4808, 4816, 4829, 4848, 4862, 4867, 4873, 4940, 4950, 4955, 4966, 4972, 4978, 4994, 5011' w/1 SPZ. Fraced w/72,000# 20/40 sand and 144,000 gal. water. Flushed w/6762 gal. water. Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED J. D. Guasco TITLE Drilling Clerk DATE March 20, 1979

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

\*See Instructions on Reverse Side

unmocc