

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐
2. NAME OF OPERATOR
Tenneco Oil Company
3. ADDRESS OF OPERATOR
P. O. Box 3249, Englewood, CO 80155
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1530' FSL 1470' FEL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) Repair casing leak ☒

SUBSEQUENT REPORT OF:

☐
☐
☐
☐
☐
☐
☐
☐
☐
☒

5. LEASE
SF-078578
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME
Florance
9. WELL NO.
45A
10. FIELD OR WILDCAT NAME
Blanco Mesaverde
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 22, T30N R8W
12. COUNTY OR PARISH
San Juan
13. STATE
NM
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
5840' gr.

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

6/22/82 - MIRUSU. Killed well w/1% KCL wtr. NDWH. NUBOP. POOH w/tbg. Tallyed in hole w/2-3/8" tbg. Tagged PBTD at 5125'. CO w/foam to 5180'. POOH. RIH w/7" pkr to 200'. PT csg, bradenhead leaking around 7" slips. Slips not sealed off. RIH w/10 stands tbg and pkr. Left open to pit.
6/23/82 - POOH w/tbg and pkr. RIH w/4-1/2" Model D pkr and set at 4200' KB. RIH w/prod. tube, seal assy, SN and 133 jts 2-3/8" tbg. Landed tbg in Model D pkr. Loaded BS w/inhibited wtr. NDBOP. NUWH. Opened well to pit. FTCU. RDMOSU.

NOTE: Received verbal approval to land tbg in packer and fill annulus with inhibited fluid from Mr. Richard Bell on 6/23/82.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Denise Wilson TITLE Production Analyst DATE 6/24/82

(This space for Federal or State office use)

APPROVED BY ACCEPTED FOR RECORD DATE _____
CONDITIONS OF APPROVAL, IF ANY:

JUL 01 1982

FARMINGTON DISTRICT *See Instructions on Reverse Side
BY J. P. Keller

NMOCC

