STATE OF NEW MEXICO ENERGY at d MINERALS DEPARTMENT

## OIL CONSERVATION DIVISION

Page 1 Revised 10/01/78

This form is not to be used for reporting packer leakage tests in Southeast New Mexico

## NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

Operator B	URLINGTON RESOURCE	S OIL & GAS CO.		Lease	SAN JUAN			Well No. 20A	
Location of Well:	Unit D Sect	35 Twp.	029N	Rge.	009W	County	SAN JUAN		
	· · · · ·	RESERVOIR OR POO	 L	TY	PE OF PROD.	METH	HOD OF PROD.	PROD. MEDIUM	
					(Oil or Gas)	(Flo	w or Art. Lift)	(Tbg. or Csg.)	
Upper Completion	FRUITLAND COAL				Gas		Flow	Tubing	
Lower Completion	MESAVERDE	ESAVERDE			Gas Flow		Flow	Tubing	
		PRE-F	LOW SHUT-IN	PRESS	URE DATA				
Upper	Upper Hour, date shut-in Length of time shut-in		-in	SI press. psig Stabilized? (			es or No)		
Completion	7/21/98	120 Ho	urs	95					
Lower Completion	7/21/98	72 Hou			280				
			FLOW TE	ST NO.		(11	1 0	wer	
	l at (hour,date)*	7/24/98			Zone producing PROD. ZONE	(Upper of	r Lower) LO	VVER	
TIME	LAPSED TIME	PRESSURE			<u> </u>		ARKS		
(hour,date)	SINCE*	Upper Completion	Lower Compl	etion	TEMP	ļ	KEM	AINS	
7/25/98	96 Hours	98	270						
7/26/98	120 Hours	100	100 185		well on shutin cycle.				
				D	ECE	WE			
					- 148 <b>2</b> 1	l is d			
				, * *			:		
Production rat	e during test	<u> </u>	<u> </u>						
Oil:	BOPD based on	Bbls. i	in	Hours		Grav.		GOR	
Gas:		MCFPD; Tested thru	(Orifice or Mete	r): 					
		MID-	TEST SHUT-IN	I PRESS	URE DATA				
Upper	MID-TEST SHUT-IN PRESSURE D Hour, date shut-in Length of time shut-in SI press. pr								
Completion				•					
Lower Completion	Hour, date shut-in	Length of time shut	ength of time shut-in		SI press. psig Stabi			es or No)	

(Continue on reverse side)

FLOW TEST NO. 2

Commenced at (hour, d	ate)**		Zone producing (Upper or Lower):					
TIME (hour, date)	LAPSED TIME SINCE "	PRESSURE		PROD. ZONE	050-040			
		Upper Completion	Lower Completion	TEMP.	REMARKS			
	<del> </del>	<u> </u>						
<del></del>								
Production rate dur	•							
Oil:	BC	PD based on	Bbls. in	Hours	Grav GOR			
Gas:		MCFPE	D: Tested thru (Or	ifice or Meter):				
Remarks:			····					
I hereby certify tha	t the information her	ein contained is true	and complete to t	he best of my knowledg	е.			
Approved		19	)	Operator Burlingto	on Resources			
	l Conservation Divis			By Alan I	Prince			
*	:	e e e e e e e e e e e e e e e e e e e		Dy	r <del>y</del> .			
Ву				Title Operations Associate				
Title		uga ora <b>t ga</b>		Date Thursday, August 06, 1998				

## NORTHWEST NEWMEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division
- 2 At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3 The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- 6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except

that the previously produced zone shall remain shut-in while the zone which was previous y shut-in is produced.

7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone

8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).