

Form 9-331
(May 1963)

1-Producing Royalties 1-GNM 1-File
UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-1

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL ☐ GAS WELL ☒ OTHER	5. LEASE DESIGNATION AND SERIAL SF 065557
2. NAME OF OPERATOR Producing Royalties, Inc.	6. IF INDIAN, ALLOTTEE OR TRIBE
3. ADDRESS OF OPERATOR Box 234, Farmington, NM 87401	7. UNIT AGREEMENT NAME
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1800' FNL - 800' FWL	8. FARM OR LEASE NAME Payne
14. PERMIT NO.	9. WELL NO. 2A
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 5790' GR	10. FIELD AND POOL, OR WILDCAT Fulcher-Kutz
	11. SEC., T., R., E., OR BLK. AND SURVEY OR AREA Sec 12 T29N R12W
	12. COUNTY OR PARISH San Juan
	13. STATE NM

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) CSG

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. **DESCRIBE PROPOSED OR COMPLETED OPERATIONS** (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

6-18-78

Ran 66 jts 2-7/8" OD 6.5# 8R EUE J-55 new tbq for csg. TE 2011.01. set @ 2010' GR. Cemented by BJ. Preflushed hole w/300 gals mud sweep. Cemented w/100 sx 2# Lodense w/1/4# cello flake per sx followed by 50 sx class "B" w/1/4# cello flake per sx. Good mud returns while cementing. Recipricated pipe OK. Maximum cementing pressure 750 psi. POB 11:15 a.m. 6-17-78.

18. I hereby certify that the foregoing is true and correct

SIGNED

Thomas A. Dugan

TITLE

Agent

DATE

6-19-78

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

*See Instructions on Reverse Side