

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	1
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

# NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. E 5184-12	
7. Unit Agreement Name	
8. Farm or Lease Name	
State Com W	
9. Well No. #19A	
10. Field and Pool, or Wildcat Blanco Mesaverde	
12. County San Juan	

## SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER-	2. Name of Operator MESA PETROLEUM CO.
3. Address of Operator P. O. BOX 2009, AMARILLO, TEXAS 79189	4. Location of Well UNIT LETTER <u>C</u> <u>1070'</u> FEET FROM THE <u>North</u> LINE AND <u>1650'</u> FEET FROM THE <u>West</u> LINE, SECTION <u>2</u> TOWNSHIP <u>30N</u> RANGE <u>8W</u> N.M.P.M.
15. Elevation (Show whether DF, RT, GR, etc.) 6334' GL	16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

### NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

### SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOBS <input type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded well @ 6:00 P.M. 6/13/78. Drilled 13 3/4" hole to 178'. Ran 5 jts of 10 3/4" 40.5# H40 ST&C csg. w/guide shoe and 2 centralizers. Set @ 178' KB. Cemented w/125 sxs Class "B", 2% Cacl.

Presently - drilling @ 1450'

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED SE Dohler TITLE Supervisor, Drlg. & Prod. DATE 6/16/78

APPROVED BY Signed by A. R. Kendrick TITLE SUPERVISOR DIST. 41 DATE 6/16/78

CONDITIONS OF APPROVAL, IF ANY:

NMOCC (3) J. Archer