## STATE OF NEW MEXICO ENERGY and MINERALS DEPARTMENT

## **OIL CONSERVATION DIVISION**

	OS aua	E		VE		Pa	
	AU6	2	1	1998	y		

This form is not to be used for reporting packer leakage tests I Scittings t New Marin

NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

OUL CON DIV.

		cace F. Mc	Kay, Jr.	Lease _	Sulliv	an	[	DID HOS	3J
ocation of Well:	Unit	Sec. 29	Twp. 29N	Rge	10W		Cou	nty <u>Sa</u>	n Juan
	NAME OF RESERVOIR OR POOL			TYPE OF P	NOO. METHOD OF PRO				
Upper Completion				Gas	5 Flow				
Lewer Pictured Cliffs			Gas	Flow			Csg.		
				OW SHUT-IN P	RESSURE D		······································		TDQ.
Upper	pper Hour, date shut-in Length of time shut-in						es or No)		
Lower	House state about to		/5 <i>DA</i>	<del>245</del>	224			YES Stabilized? (Yes or No)	
Lower Completion	Į.	17-12-98	2204	lys .	144			YES	
				FLOW TEST			······································		
ommence	s at thour, dat	o)*			Zone preduc	ning (Uppe	r or Lowert		
TIME (hour, date)		LAPSED TIME SINCE®			PROD. ZONE		REMARKS		
1612/	7-27-98	0	224	147			UPPER	ZONE	Pizopucina
1600	/7-25 <b>.1</b> 19	3 23.8 HR	225	147					
85+/	7-29-98	40.7 HZ	726	148			. '		
624/	8·3-98	168.2HZ	224	146			· · · ·	d :	·
	<del></del>							•	
							= Line	PResso	ule
roducti	on rate di	ring test		•					-
)ii: <u> </u>	A\r	BOPI	D based on	Bbls. in	F	lours.	G	rav	GOR
<del>)</del> 25:			MCF	•					
		•	MID-TE	ST SHUT-IN PE	RESSURE DA	ATA			·
Upper ompletion	Upper					SI press. peig		Stabilized? (Yes or No)	
	Hour date at		I speth of time shu						

FLOW TEST NO. 2

TMAS	LAPSED TIME	, PRESENTE		PROD. 20NE	REMARKS		
(hour, date)	SINCE **	Upper Completion	Lower Completion	TEMP.	NEMANAS		
!							
,							
		-					
	<u> </u>						
			I				
				<u> </u>			
	Į						
		<del> </del>		<u> </u>			
		l					
-	- <del></del>				•		
Production rate d	luring test						
0.1.	BOD.	D based on	Bble in	. Hours	Grav GOR		
Gas:		ма	PD: Tested thru	(Orifice of Meter	·):		
					•		
Remarks:	<u> </u>		,				
I hereby certify t	hat the informat	ion herein contait	ned is true and co	omplete to the be	st of my knowledge.		
		<u>~</u> '	10	O Ho	ZACE F. MEKM, JR.		
	il Conservation			-			
New Mexico C			•	Rv ////	Bee		
	AUG 2	1 1998		- ·			
Ву		1 1770		Title <u>AGENT</u>	FOR HORAGE F. MªKAY JE.		
-, <del></del>		GAS INSPECTOR, D	ICT #8				
Title				Date <u>8/19/98</u>	)		

## NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

 A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.

rd at thour, date) # \*

- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Text No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shur-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- 6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except

- that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tens must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midday point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Axtec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).