

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN DUPLICATE*

(See other in-
structions on
reverse side)Form approved.
Budget Bureau No. 42-R355.5.

WELL COMPLETION OR RECOMPLETION REPORT AND LOG *

1a. TYPE OF WELL:		OIL WELL ☐	GAS WELL ☒	DRY ☐	Other _____		
b. TYPE OF COMPLETION:		NEW WELL ☒	WORK OVER ☐	DEEP-EN ☐	PLUG BACK ☐	DIFF. RESVR. ☐	Other _____
2. NAME OF OPERATOR <i>SUPRON ENERGY CORPORATION</i>						7. UNIT AGREEMENT NAME	
3. ADDRESS OF OPERATOR <i>P.O. Box 808, Farmington, New Mexico 87401</i>						8. FARM OR LEASE NAME <i>Largo Federal</i>	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements)* At surface <i>1065 ft./South; 815 ft./West line</i> At top prod. interval reported below <i>Same as above.</i> At total depth <i>Same as above.</i>						9. WELL NO. <i>2</i>	
14. PERMIT NO.						DATE ISSUED	
12. COUNTY OR PARISH <i>San Juan</i>						13. STATE <i>New Mexico</i>	

15. DATE SPUNDED <i>7-18-79</i>	16. DATE T.D. REACHED <i>7-23-79</i>	17. DATE COMPL. (Ready to prod.) <i>9-17-79</i>	18. ELEVATIONS (DF, REB, RT, GR, ETC.)* <i>5837 R.K.B.</i>	19. ELEV. CASINGHEAD <i>5828</i>	
20. TOTAL DEPTH, MD & TVD <i>2475 MD & TVD</i>	21. PLUG BACK T.D., MD & TVD <i>2355</i>	22. IF MULTIPLE COMPL., HOW MANY* <i>----</i>	23. INTERVALS DRILLED BY <i>→</i>	ROTARY TOOLS <i>0 - 2475</i>	CABLE TOOLS
24. PRODUCING INTERVAL(S), OF THIS COMPLETION—TOP, BOTTOM, NAME (MD AND TVD)* <i>2162 - 2202 Pictured Cliffs</i>					25. WAS DIRECTIONAL SURVEY MADE <i>No</i>
26. TYPE ELECTRIC AND OTHER LOGS RUN <i>Induction - SFL & Compensated Density</i>					27. WAS WELL CORED <i>No</i>

28. CASING RECORD (Report all strings set in well)					
CASING SIZE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
<i>7.625</i>	<i>26.40</i>	<i>212</i>	<i>9-7/8"</i>	<i>100 sx "B" w/2% CaCl</i>	
<i>2.875</i>	<i>6.50</i>	<i>2387</i>	<i>6-3/4"</i>	<i>125 sx Howco Lite</i>	
				<i>50 sx "B" w/2% CaCl</i>	

29. LINER RECORD					30. TUBING RECORD		
SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*	SCREEN (MD)	SIZE	DEPTH SET (MD)	PACKER SET (MD)

31. PERFORATION RECORD (Interval, size and number) <i>11 - 0.30" holes at each of the following depths: 2162, 2167, 2170, 2174, 2178, 2182, 2186, 2190, 2194, 2198, 2202.</i>	32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC. DEPTH INTERVAL (MD) <i>2162 - 2202</i> AMOUNT AND KIND OF MATERIAL USED <i>192 bbl. 2% KCL water, 249,000 SCF of Nitrogen, & 30,000 lb. of 20 - 40 sand. 500 gal. 7½% HCL.</i>
--	---

33.* PRODUCTION							
DATE FIRST PRODUCTION		PRODUCTION METHOD (Flowing, gas lift, pumping—size and type of pump)				WELL STATUS (Producing or shut-in) <i>Shut-in</i>	
DATE OF TEST <i>9-17-79</i>	HOURS TESTED <i>3</i>	CHOKE SIZE <i>3/4"</i>	PROD'N. FOR TEST PERIOD <i>→</i>	OIL—BBL. <i>219</i>	GAS—MCF. <i>6</i>	WATER—BBL.	GAS-OIL RATIO
FLOW. TUBING PRESS.	CASING PRESSURE <i>131</i>	CALCULATED 24-HOUR RATE <i>→</i>	OIL—BBL.	GAS—MCF. <i>1750</i>	WATER—BBL.	OIL GRAVITY-API (CORR.)	

34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.) <i>Vented</i>				TEST WITNESSED BY <i>John C. Rector</i>			
35. LIST OF ATTACHMENTS							

36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records

SIGNED *Kenneth E. Roddy* TITLE *Production Superintendent* DATE *September 24, 1979*

*(See Instructions and Spaces for Additional Data on Reverse Side)

444000

INSTRUCTIONS

General: This form is designed for submitting a complete and correct well completion report and log on of lands and leases to a Federal agency or a State agency, or both, pursuant to applicable Federal and/or State laws and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office. See instructions on items 22 and 24, and 33, below regarding separate reports for separate completions.

If not filed prior to the time this summary record is submitted, copies of all currently available logs (drillers, geologists, sample and core analysis, all types electric, etc.), formation and pressure tests, and directional surveys, should be attached hereto, to the extent required by applicable Federal and/or State laws and regulations. All attachments should be listed on this form, see item 35.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 18: Indicate which elevation is used as reference (where not otherwise shown) for depth measurements given in other spaces on this form and in any attachments.

Items 22 and 24: If this well is completed for separate production from more than one interval zone (multiple completion), so state in item 22, and in item 24 show the producing interval, or intervals, top(s) and bottom(s) (if any) for only the interval reported in item 33. Submit a separate report (page) on this form, adequately identified, for each additional interval to be separately produced, showing the additional data pertinent to such interval.

Item 29: "Sacks Cement": Attached supplemental records for this well should show the details of any multiple stage cementing and the location of the cementing tool.

Item 33: Submit a separate completion report on this form for each interval to be separately produced. (See instruction for items 22 and 24 above.)

37. SUMMARY OF POROUS ZONES: SHOW ALL IMPORTANT ZONES OF POROSITY AND CONTENTS THEREOF: CORED INTERVALS; AND ALL DRILL-STEM TESTS, INCLUDING DEPTH INTERVAL TESTED, CUSHION USED, TIME TOOL OPEN, FLOWING AND SHUT-IN PRESSURES, AND RECOVERIES			38. GEOLOGIC MARKERS			
FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.	NAME	MEAS. DEPTH	TRUE VERT. DEPTH
				Base Ojo Alamo	1220	1220
				Top Pictured C.	2154	2154