

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE\*  
(Other instructions on re-  
verse side)

Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

SF 080000-A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

-----

7. UNIT AGREEMENT NAME

None

8. FARM OR LEASE NAME

Simmons "E"

9. WELL NO.

1-A

10. FIELD AND POOL, OR WILDCAT

Blanco Mesaverde

11. SEC., T. R., M., OR BLK. AND  
SURVEY OR AREA

Sec.26 - T29N - R9W

N.M.P.M.

12. COUNTY OR PARISH 13. STATE

San Juan

New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL ☐ GAS ☒ OTHER ☐  
WELL WELL

2. NAME OF OPERATOR

D.J. Simmons

3. ADDRESS OF OPERATOR

3815 McCart Street  
Fort Worth, Texas 76110

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)

At surface 1685' FSL - 1470' FEL Sec.26 - T29N - R9W

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

5800 GL 5814 KB

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON\*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT\*

(Other) Set Surf, Intermed, & liner x

(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any  
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-  
nent to this work.)

6-3-79 Spudded 13 3/4" surf. hole & mud drilled to approx. 347'.  
6-4-79 ran 322' of 9 5/8", 36# K-55 surf. csg. set at 337' & cemented with  
240 sx. Cl."B" + 2%CaCl. Cement cir. to surf. Nippled up, installed Shaffer  
10"-900 Ser., hydraulic closing double ram, 6000 psi test B.O.P. & tested surf.  
to 600 psi, held steady for 30 min. Then, after approx. 9 hrs. of cement set,  
started mud drilling 8 3/4" hole to a depth of 2718' reached 6-6-79. 6-7-79  
ran 2718' pf 7" 20# K-55 casing set at 2717' & cemented with 250 sx of 50-50  
Poz. & 150 sx of Cl "B" cement. Tested csg. to 1500 psi & held 5 min, OK.  
6-7-79 drilled from under 7" intermediate with gas & drilled a 6 1/4" hole to  
approx. 5011' T.D. 6-10-79. 6-10-79 ran Induction-Gamma & Compensated Density  
logs. Log tops: Surf.- Nacimiento, Ojo Alamo-1234', Fruitland 1909',  
Pictured Cliffs 2248', Cliff House 3930', Menefee 4012', Point Lookout 4518'  
T.D. 5011' 6-11-79 ran 4 1/2", 10.5# K-55 liner set at T.D. 5011' back up to  
2489' (top of liner), and cemented with 325 sx of 50-50 Poz. cement. Cement  
circulated to top of liner. Well shut in awaiting completion. ~~xxxxxx~~

18. I hereby certify that the foregoing is true and correct

SIGNED

*Ashton B. Geren, Jr.*  
Ashton B. Geren, Jr.

Manager & Supt. for:

TITLE D.J. Simmons

DATE Sept. 14, 1979

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE