

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other ☐

2. NAME OF OPERATOR
Energy Reserves Group, Inc.

3. ADDRESS OF OPERATOR
P. O. Box 3280 Casper, Wyoming 82602

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 980' FSL & 920' FWL (SW SW)
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:	SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF <input type="checkbox"/>	<input type="checkbox"/>
FRACTURE TREAT <input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE <input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL <input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE <input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES <input type="checkbox"/>	<input type="checkbox"/>
ABANDON* <input type="checkbox"/>	<input type="checkbox"/>
(other) <u>Well History</u>	

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

The above described well was spudded at 3:00 p.m., 9-4-79.
Drilled 12 $\frac{1}{4}$ " hole to 122'. Ran 3 jts 8 5/8" O.D., 36#, J-55, R-3, ST&C New casing set @ 118' (K.B.). Cemented w/100 sx Class "B" cement w/2% CaCl₂. Plug down @ 11:50 p.m., Good cement returns.
Nippled up & pressure tested BOPE to 600 PSI, held O.K.
Drilled 6 3/4" hole to 1,700' and ran logs.
Ran 42 jts 4 $\frac{1}{2}$ " O.D., 10.79#, 8Rth, BE, ST&C, New casing set @ 1,673' (K.B.).
Cemented w/50 sx 65-35% pozmix w/12% gel & 1/4# Flocele/sx; followed by 200 sx of Class "B" cement w/1/4# Flocele/sx. Plug down @ 5:15 p.m., 9-8-79. Good cement returns. Rig released @ 7:00 pm.m, 9-8-79.
9-9-79 - W.O.C. & W.O.C.T.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED R.C. Milligan TITLE Drlg. Supt. DATE 9-10-79

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY: