NO. OF COPIES RECEIVED	3	Form C-103 Supersedes Old
DISTRIBUTION		C-102 and C-103
SANTA FE	NEW MEXICO OIL CONSERVATION COMMISSION	Effective 1-1-65
FILE		5a. Indicate Type of Lease
U.S.G.S.		State Fee XX
LAND OFFICE	<del>                                      </del>	5. State Oil & Gas Lease No.
OPERATOR		
	AND THE PERSON OF THE PERSON O	
(DO NOT USE THIS FO USE	SUNDRY NOTICES AND REPORTS ON WELLS ORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. "APPLICATION FOR PERMIT —" (FORM C-101) FOR SUCH PROPOSALS.)	7. Unit Agreement Name
OIL GAS WELL WELL	L XX OTHER-	Gallegos Canyon Unit
. Name of Operator		
Energy Reserves	Group, Inc.	Gallegos Canyon Unit
. Address of Operator		
	Casper, Wyoming 82602	10. Field and Pool, or Wildcat
1. Location of Well	7540	
UNIT LETTERO	800 FEET FROM THE South LINE AND 1540 FEET FE	ROM KUEZ PICEUFED CITIES WE
	LINE, SECTION 30 TOWNSHIP 29N RANGE 12W NM	
		12. County
	15. Elevation (Show whether DF, RT, GR, etc.)	San Juan
	G.L 5381', K.B 5391'	
16. NOTI	Check Appropriate Box To Indicate Nature of Notice, Report or INTENTION TO: SUBSEQUE	Other Data ENT REPORT OF:
PERFORM REMEDIAL WORK	PLUG AND ABANDON REMEDIAL WORK	ALTERING CASING
TEMPORARILY ABANDON	COMMENCE DRILLING OPNS.	PLUG AND ABANDONMENT
PULL OR ALTER CASING	CHANGE PLANS CASING TEST AND CEMENT JQB	Well History
	OTHER	well History X
OTHER		
	Completed Operations (Clearly state all pertinent details, and give pertinent dates, inclu-	ding estimated date of starting any proposed
<ol> <li>Describe Proposed or C work) SEE RULE 1903.</li> </ol>	ompleted Operations (Clearly state all pertinent details, and give pertinent dates, there.	aving copyrimated and ty command and the t
	ribed well was spudded at 11:00 p.m., 9-8-79.	
n:1102 124" h	ole to 130'. Ran 3 jts. 8 5/8" O.D., 36#, J-55, R-3,	SS, ST&C, 8Rth
Drilled 12% III	at 126' (K.B.). Cemented w/100 sx of Class "B" cemented	nt w/2% CaCl2.
New Casing Set	1:00 a.m., 9-9-79. Good cement returns.	
Plug down at 1.	1:00 a.m., 9-9-79. Good coment recarns.	
	The same to stod POPE to 600 PST held O K	
Nippled up and	pressure tested BOPE to 600 PSI, held O.K.	
	the second term of the second	
Drilled 6 3/4"	hole to 1550' (K.B.) and ran logs.	
Ran 38 jts 4½"	O.D., 10.79#, BE, 8Rth, SS, R-3, New Casing set at 5-35 pozmix w/12% gel & ½# Flocele/sx, followed by 11	1535' (R.B.). Cemented 5 sx of Class "B" Cement
w/100 sx or 65 w/l¼" Flocele/	/sx. Plug down at 10:00 p.m., 9-13-79. Good returns.	
9-14-79 - W.O.	.C. & W.O.C.T.	
18. I hereby certify that the	e information above is true and complete to the best of my knowledge and belief.	
. /	$\rho Q$	
hllen	B. Darwer TITLE _ Dist. Prod. Eng RMD	9-26-79
SIGNED Y CLU	1116	
- J Siom	ned by A. R. Kendrick	SEP 28 1079
- #IBH	TITLE SUPERVISOR DISTRICT # 5	DATE
A D D D O V F D B Y		

APPROVED BY ....

CONDITIONS OF APPROVAL, IF ANY: