

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	1
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>		7. Unit Agreement Name
2. Name of Operator Amoco Production Company		8. Farm or Lease Name State Gas Com "BQ"
3. Address of Operator 501 Airport Drive Farmington, NM 87401		9. Well No. 1
4. Location of Well UNIT LETTER <u>I</u> , <u>1850</u> FEET FROM THE <u>South</u> LINE AND <u>870</u> FEET FROM THE <u>East</u> LINE, SECTION <u>32</u> TOWNSHIP <u>29N</u> RANGE <u>13W</u> NMPM.		10. Field and Pool, or Wildcat Basin Dakota
15. Elevation (Show whether DF, RT, GR, etc.) 5867' GL		12. County San Juan

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER <u>Spud & Set Surface Casing</u> <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded well on 9-25-79. Drilled to 291' and set 8-5/8", 24 pound surface casing at 291'. Cemented casing with 315 sxs class "B" Neat cement containing 2% CaCl₂.

Presently drilling 7-7/8" hole to TD.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Original Signed By E. SVOBODA TITLE Dist. Adm. Supr. DATE 10-8-79

APPROVED BY Original Signed by A. R. Harbison TITLE DATE

CONDITIONS OF APPROVAL, IF ANY: