

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other

2. NAME OF OPERATOR
Southland Royalty Company

3. ADDRESS OF OPERATOR
P.O. Drawer 570, Farmington, N.M. 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1520' FNL & 1110' FWL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) Casing Report

SUBSEQUENT REPORT OR

☐
☐
☐
☐
☐
☐
☐
☐
☐
☐
☒

RECEIVED
APR 1 1981

U. S. GEOLOGICAL SURVEY
FARMINGTON, N. M.

(NOTE: Report results of multiple completion or zone change on Form 9-330)

5. LEASE
SF-077056

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Cozzens "C"

9. WELL NO.
1-E

10. FIELD OR WILDCAT NAME
Basin Dakota


11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Section 20, T29N, R11W

12. COUNTY OR PARISH
San Juan

13. STATE
New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
5557' GR



17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

9/05/80 Ran 156 joints (6460') of 5-1/2", 15.50#, K-55 casing set at 6445'. DV tools at 1808' and 4396'. Cemented as follows:
Cemented 1st Stage with 219 sacks of Class "B" 50/50 Poz with 6% gel, 1/4# celloflake per sack and .6% Halad 9. Plug down at 1:45 P.M. 9-5-80.
Cemented 2nd Stage with 335 sacks of Class "B" 50/50 Poz with 6% gel, 1/4# celloflake per sack and .6% Halad 9. Plug down at 4:00 P.M. 9-5-80.
Cemented 3rd Stage with 185 sacks of Class "B" 50/50 Poz with 6% gel. Plug down at 7:30 P.M. 9-05-80. TOC @ 2684'.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Arthur Dwyer TITLE Drilling Clerk DATE March 31, 1981

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

NMOCC

APR 2 1981