5. LEASE

## **UNITED STATES** DEPARTMENT OF THE INTERIOR

DEPARTMENT OF THE INTERIOR	NM - 0702
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS  (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	7. UNIT AGREEMENT NAME
1 4	8. FARM OR LEASE NAME
well gas described well well other	_Wilson 9. WELL NO
2. NAME OF OPERATOR	2
SUPRON ENERGY CORPORATION	10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR	Aztec Chacra
P.O. Box 808, Farmington, New Mexico 87401	Undesignated Fruitland Ext. 11. SEC., T., R., M., OR BLK. AND SURVEY OF
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)	AREA  Sec. 31, T-29N, R-10W, N.M.P.M
AT SURFACE: 1635 ft./N ; 1550 ft./E line	12. COUNTY OR PARISH 13. STATE
AT TOP PROD. INTERVAL: Same as above.	San Juan New Mexico
Same as above.	14. API NO.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)
DECLIEST FOR APPROVAL TO	5582 GR.
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: L TEST WATER SHUT-OFF	
FRACTURE TREAT	
SHOOT OR ACIDIZE	
REPAIR WELL	(NOTE: Report results of multiple completion or zone
PULL OR ALTER CASING	change on Form 9–330.)
CHANGE ZONES	
ABANDON*	
(other)	
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state including estimated date of starting any proposed work. If well is dis	all pertinent details, and give pertinent dates
including estimated date of starting any proposed work. If well is directly measured and true vertical depths for all markers and zones pertinent	ectionally drilled, give subsurface locations and
1. Spudded 9-7/8" surface hole at 7:00 p.m. 2-	-27-80.
2. Drilled 9-7/8" surface hole to total depth	of 203 feet R.K.B.
3. Ran 5 joints of 7-5/8", 26.40#, K-55 casing	Landed at 203 ft R.K.B.
4. Cemented with 85 sacks of class "B" with 3% Plug down at 9:15 a.m. 2-28-80. Cement cir	Calcium Chlorede
5. Waited on cement for 12 hours.	Urner 1
6. Pressure-tested casing to 800 PSI for 15 mi	nutes. Held MAR 71980
	DIST. 3
Subsurface Safety Valve: Manu. and Type	Set @ Ft.
18. I hereby certify that the foregoing is frue and correct	Set @ Ft.
SIGNED Flower Froduction Supt	
(This space for Federal or State office	use)
APPROVED BY TITLE	DATE TO BE TO BE
CONDITIONS OF APPROVAL, IF ANY:	LECEPTED FOR NECORO
NIARO	
1400 <b>0</b> .	MAR 5 1980

\*See Instructions on Reverse Side

FARMINGTON DISTRICT
BY ML Ruchera