Form Approved. Budget Bureau No. 42-R1424

UNITED STATES DEPARTMENT OF THE INTERIOR	5. LEASE SF-076465	
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME	
Do not use this form for proposals to drill or to deepen or plug back to a different eservoir. Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME	
1. oil gas 🗊	Beck "A"	
1. oil gas k other	9. WELL NO.	
2. NAME OF OPERATOR	1-E	
Southland Royalty Company	10. FIELD OR WILDCAT NAME	
3. ADDRESS OF OPERATOR	Basin Dakota	
P.O. Drawer 570, Farmington, New Mexico	11. SEC., T., R., M., OR BLK. AND SURVEY OR	
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	AREA	
halow)	Section 10, T29N, R12W	
AT SURFACE: 870' FNL & 1760' FEL	12. COUNTY OR PARISH 13. STATE	
AT TOP PROD. INTERVAL:	San Juan New Mexico	
AT TOTAL DEPTH:	14. API NO.	
6. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,		
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)	
AUDOFOLIENT DEPONT OF	5694 GR	
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF		
TEST WATER SHUT-OFF		
PHOOT OF ACIDITE		
REPAIR WELL JAN	(NOTE: Report results of multiple dompletion of zame)	
PULL OR ALTER CASING \(\Bar{\cappa} \)	change on Form 9-130//	
MULTIPLE COMPLETE U. S. GTOLS	(NOTE: Report results of multiple dompletion of zdrier change on Form 9–130)// ON. N. CON. S. CON.	
CHANGE ZONES	DIST. COM	
ABANDON* (other) Spud & Casing Report X	\ '.3 M	
17 DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state	te all pertinent details, and give pertinent dates,	

- 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*
- 1/5/81 Spudded 12-1/4" surface hole at 7:30 P.M. 1-5-81 and drilled to a Total Depth 242'. Ran 5 joints (225.11') of 8-5/8", 24#, K-55 casing set at 240'. Cemented with 150 sacks of Class "B" with 1/4# gel flake per sack and 3% CaCl₂. Plug down at 3:00 A.M. 1-6-81. Cement circulated to surface.

Subsurface Safety Valve: Manu. and Type		Set @ Ft.
I will all the foregoing is t		Jan 6. 1980
<i>U</i> (/	(This space for Federal or State office use)	
JAN 0 8 1981	TITLE DATE	
CONDITIONS OF APPROVAL, IF ANY: FARMINGTON DISTRICT	NMOCG	