

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well gas well other

2. NAME OF OPERATOR
Southland Royalty Company

3. ADDRESS OF OPERATOR
P.O. Drawer 570, Farmington, N.M. 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1620' FSL & 1525' FEL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

5. LEASE
SF-077056

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Cozzens "B"

9. WELL NO.
1-E

10. FIELD OR WILDCAT NAME
Basin Dakota

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Section 19, T29N, R11W

12. COUNTY OR PARISH | 13. STATE
San Juan | New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB AND WND)
5484' GR

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL



PULL OR ALTER CASING

MULTIPLE COMPLETE

CHANGE ZONES

ABANDON*

(other) Casing Report



17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

2/05/81 Ran 196 joints (6255.08') of 4-1/2", 10.5#, K-55 casing set at 6260'. DV tools at 4285' and 1718'.

2/06/81 Cemented 1st Stage with 204 sacks of Class "B" 50/50 Poz with 1/4# flocele per sack and 6% gel, followed with 50 sacks of Class "B" and 2% CaCl₂. Plug down at 8:15 A.M. 2-06-81.
Cemented 2nd Stage with 266 sacks of Class "B" 50/50 Poz with 6% gel, followed with 50 sacks of Class "B" and 2% CaCl₂. Plug down at 10:45 A.M. 2-06-81.
Cemented 3rd Stage with 236 sacks of Class "B" 50/50 Poz with 6% gel. Plug down at 1:15 P.M. 2-06-81.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct
SIGNED Retina Johnson TITLE Drilling Clerk DATE Feb. 9, 1981
ACCEPTED FOR RECORD

APPROVED BY FEB 17 1981 TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

FARMINGTON DISTRICT
BY [Signature]