

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐
well well2. NAME OF OPERATOR
Energy Reserves Group, Inc.3. ADDRESS OF OPERATOR
P.O. Box 3280, Casper, Wyoming 826024. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1620' FSL & 900' FEL (NE-SE)
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐ Well History ☒

SUBSEQUENT REPORT OF:

☐
☐
☐
☐
☐
☐
☐
☐
☐
☒RECEIVED
FEB 12 1980U. S. GEOLOGICAL SURVEY
FARMINGTON, N.M.

(Notes: Report results of multiple completion or zone change on Form 9-330.)

5. LEASE

SF-080723

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

Gallegos Canyon Unit

8. FARM OR LEASE NAME

Gallegos Canyon Unit

9. WELL NO.

301

10. FIELD OR WILDCAT NAME

West Kutz Pictured Cliffs

11. SEC., T., R., M. OR BLK. AND SURVEY OR AREA

Sec. 20- T29N-R12W

12. COUNTY OR PARISH 13. STATE

San Juan

New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

L. 5522' K.B. 5532'

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

The above referenced well was spudded (8:00 P.M., 1-21-80.

Drilled 12 1/4" hole to 135' K.B. and ran 3 jts. 8-5/8" O.D., 24#, K55, 8Rth, R3, ST&C, new casing set @ 130' K.B. Cemented w/100 sx Class B cement w/3% CACL₂ and 1/4# Flocele/sk. Plug down @ 5:30 AM 1-22-80. Good cement returns.

Nippled up and pressure tested BOPE to 600 P.S.I. - Held O.K.

Drilled 6-3/4" hole to 1741' KB and ran logs

Ran 52 jts, 4 1/2" O.D., 10.5# & 11.6#, K-55 & CW55, R 283, 8 Rth, ST&C, New casing set @ 1741" K.B. - Cemented w/400sx 50-50 Pozmix and cement w/1/4# Flocele/sx. Plug down @ 6:15 P.M. 1-25-80 Good cement returns - 1-28-80 W.O.C. & W.O.C.T.

Subsurface Safety Valve: Manu. and Type

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Drilling Foreman

DATE January 28, 1980

ACCEPTED FOR RECORD

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

FEB 15 1980

NMOCG

FARMINGTON DISTRICT
BY M. L. Kuchera

*See Instructions on Reverse Side

U. S. GEOLOGICAL SURVEY
FEB 22 1980