Fort Approved	
Byoget Bureau No	47-R1474
7	

Form 5-331	Byoget Bureau No. 47-R1474
UNITED STATES	5. LEASE
DEPARTMENT OF THE INTERIOR	NM 020503
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–33)—C for such proposals.)	8. FARM OR LEASE NAME
	Federal
1. oil gas well other	9. WELL NO.
2. NAME OF OPERATOR	10E
Mesa Petroleum Co.	10. FIELD OR WILDCAT NAME
3 ADDRESS OF OPERATOR	Basin Dakota
1660 Lincoln St., #2800, Denver, Colo. 80264	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	Sec. 1, T29n, Rllw
halow)	12. COUNTY OR PARISH 13. STATE
AT SURFACE: 1240' FNL & 1745' FEL	1
AT TOP PROD. INTERVAL:	San Juan New Mexico
AT TOTAL DEPTH: Same	14. API NO.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	15. ELEVATIONS (SHOW DF, KDB, AND WD)
REPORT, OR OTHER DATA	5869 GL
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	3809 GL
TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL PULL OR ALTER CASING MULTIPLE COMPLETE CHANGE ZONES ABANDON* (other) Change plans and mud drill this well	(NOTE: Report results of multiple completion or zone change on Form 9–330.)
 DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly sta including estimated date of starting any proposed work. If well is measured and true vertical depths for all markers and zones pertine 	te all pertinent details, and give pertinent dates, directionally drilled, give subsurface locations and int to this work.)*
Mesa Petroleum Co. plans to drill a 12 1/4" h new K-55 STC casing to total depth and cement 2% CaCl. WOC 8 hrs. and test BOP's to 800 ps casing shoe.	i. prior to drilling the surface
Drill a 7 7/8" hole to approximately 6,500', 1/2" 10.5#/ft. new K-55 STC casing to total of 50 Pos mix, 2% Gel.	run electric logs to TD, set 4 Hepth and cement with 850 sxs. 50
The wall will be drilled using fresh water ar	nd chemical gel to total depth.

The well will be drilled using fresh water and chemical gel to total depth.

Subsurface Safety Valve: Manu, and Type	Set @ Ft.
SIGNED JULY LAND TITLE DIV. Dr.	g. Super. DATE - May 16, 1980
(This space for Federal or	State office use)
APPROVED BY TITLE TOUR TOUR SOLUTIONS OF APPROVAL, IF ANY:	DATE

xc 5/16/80: TLS, Div. Files, J. Archer, St. of NM