

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

CONOCO INC.

3. Address and Telephone No.

10 DESTA DR. STE. 100W, MIDLAND, TX. 79705-4500 (915) 686-5424

4. Location of Well (Footage Sec., T R M or Survey Description)

1275' FNL & 1745' FEL
G Sec. 1, T-29N, R-11W

5. Lease Designation and Serial No.

NMNM 020503

6. If Indian, Allottee or Tribe Name

7. If Unit or C.A. Agreement Designation

8. Well Name and No.

Federal No. 10E

9. API Well No.

30-045-24058

10. Field and Pool, or Exploratory Area

Blanco Mesaverde (72319)

11. County or Parish, State

San Juan, NM

CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☒ Notice of Intent
☐ Subsequent Repon
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☒ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other

- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracrunng
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Repon result of multiple completion well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

It is proposed to squeeze off the Fruitland Coal, recomplete this well to the Mesaverde, and then to downhole commingle with the Dakota as follows:

1. A CIBP is already set at 2345' below the Fruitland Coal. Set a treating packer @ 2000' above the Fruitland Coal.
2. Squeeze the Fruitland Coal with 130 sxs of cement
3. Drill out cement and pressure test squeeze to 1000 psi.
4. Drill out CIBP @ 2345'.
5. Set CIBP @ approximately 5500' above the Dakota.
6. Perforate Mesaverde from 4164'-4745' w/1 shot per foot
7. Set frac liner over the squeezed Fruitland Coal and slick water frac Mesaverde.
8. POOH with frac liner, put Mesaverde on production, and test.
9. After sufficient production testing is completed to develop an allocation formula, drill out CIPB @ 5500' and commingle with Dakota.

Downhole commingling was approved 1/12/97.

NOTE: This is a revised recompletion procedure to the one approved 7/3/94.

RECEIVED
DEC 29 1997

OIL CON. DIV.
DIST. 3

14. I hereby certify that the foregoing is true and correct

Signed

Jerry W. Hoover

Title

Jerry W. Hoover
Sr. Conservation Coordinator

Date

12/16/97

(This space for Federal or State office use)

Approved by

Duane W. Spencer

Title

Date

DEC 22 1997

Conditions of approval if any