

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

RECEIVED
MAR - 9 1995
OIL CON. DIV.
DIST. 3

Sundry Notices and Reports on Wells

1. Type of Well

GAS

2. Name of Operator

SOUTHLAND ROYALTY COMPANY

3. Address & Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M

1540'FSL, 1655'FEL, Sec.18, T-29-N, R-11-W, NMPM

5. Lease Number

SF-077056

6. If Indian, All. or Tribe Name

7. Unit Agreement Name

8. Well Name & Number
Cozzens #6E

9. API Well No.

30-045-24127

10. Field and Pool

Basin Dakota

11. County and State

San Juan Co, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

Type of Action

☐ Notice of Intent☐ Abandonment☐ Change of Plans☒ Subsequent Report☐ Recompletion☐ New Construction☐ Final Abandonment☐ Plugging Back☐ Non-Routine Fracturing☐ Casing Repair☐ Water Shut off☐ Altering Casing☐ Conversion to Injection☒ Other -

13. Describe Proposed or Completed Operations

- 2-10-95 MIRU. PT tbg to 450 pis, OK. PT csg to 1100 psi, OK. Pump 10 bbl 2% KCl wtr down tbg. ND WH. NU BOP. POOH w/206 jts 2 3/8" tbg. SDON.
- 2-11-95 TIH w/5 1/2" csg scraper to 3530'. Pump 10 bbl KCl down tbg. TIH to 6310'. TOO. TIH w/RBP & pkr. Set RBP @ 6100'. Roll hole w/KCl wtr. Set pkr @ 6040'. PT RBP to 1000 psi, OK. PT csg to 1000 psi/15 min, OK. TOO. w/RBP @ pkr. SDON.
- 2-12-95 TIH, tag fill @ 6310'. CO to RBP @ 6345'. Mill on CIBP. Ream hole @ 6345-6458'. Clean hole. TOO. SDON.
- 2-13-95 TIH w/cmt retainer, set @ 6410'. Load backside w/30 bbl KCl wtr. Establish injection. TOO. TIH w/FB pkr, set @ 6372'. TOO. SDON.
- 2-14-95 TIH w/cmt retainer, set @ 6374'. Load tbg w/30 bbl 2% KCl wtr, 5 bbl fresh wtr. Pump 5 bbl Class "G" neat cmt slurry, displace w/24.4 bbl wtr. Leave 1/4 bbl cmt in tbg. TOO. TIH to 5300'. WOC. SDON.
- 2-15-95 TIH to 6310'. Tag cmt. Drill out cmt to cmt retainer @ 6373'. Blow well & CO.
- 2-16-95 Blow well. TIH w/SAP tool. Set pkr @ 6100'. PT csg to 1000 psi, OK. Spot 300 gal 15% HCl, set SAP tool. Pressure up, split tbg. TOO. Replace split jt. Break down perfs. SDON.
- 2-17-95 TOO. w/pkr. TIH to 6358'. Blow well & CO.
- 2-18-95 Blow well & CO. TOO. TIH to 6358'. TOO. TIH w/113 jts 2 3/8" 4.7# J-55 tbg, landed @ 6330'. ND BOP. NU WH. RD. Rig released.

14. I hereby certify that the foregoing is true and correct.

Signed

Title Regulatory Affairs

Date 2/24/95

(This space for Federal or State Office use)

APPROVED BY

Title

Date

CONDITION OF APPROVAL, if any:

ACCEPTED FOR RECORD

FEB 24 1995

FARMINGTON DISTRICT OFFICE

NMOC

3V