UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY SUNDRY NOTICES AND REPORTS ON WELLS DE THE LIMIT FORM 19-331— for such proposals, or will be compared to a different state for the proposals, or will be compared to the form 19-331—for such proposals, or will be compared to the form 19-331—for such proposals, or there is well well well well well well well wel		
SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to deepen or plug back to a different service. We form for proposals to drill or to deepen or plug back to a different service. We form for proposals to drill or to deepen or plug back to a different service. We form for proposals to drill or to deepen or plug back to a different service. We form for proposals to drill or to deepen or plug back to a different service. We form for proposals to drill or to deepen or plug back to a different service. We form for proposals to drill or to deepen or plug back to a different service. We form for proposals to drill or to deepen or plug back to a different service. We form for proposals to drill or to deepen or plug back to a different service. We form for proposals to drill or to deepen or plug back to a different service. We form for proposals to drill or to deepen or plug back to a different service. We form for proposals to drill or to deepen or plug back to a different service. We form for	DEPARTMENT OF THE INTERIOR	S. LEASE.
SUNDRY NOTICES AND REPORTS ON WELLS o not use this form for proposals to drift or to deepen or plug back to a different servoir. Use Form 9-331-6 for such proposals to drift or to deepen or plug back to a different servoir. Use Form 9-331-6 for such proposals to drift or to deepen or plug back to a different servoir. Use Form 9-331-6 for such proposals to drift or to deepen or plug back to a different servoir. Use Form 9-331-6 for such proposals to drift or to deepen or plug back to a different servoir. We form 9-331-6 for such proposals to drift or the servoir. We form 9-331-6 for such proposals to drift or to deepen or plug back to a different servoir. We form 9-331-6 for such proposals to drift or the servoir. We form 9-331-6 for such proposals to drift or the servoir. We form 9-331-6 for such proposals to drift or the servoir. We form 9-331-6 for such proposals to drift or the servoir. We form 9-331-6 for such proposals to drift or the servoir. We form 9-331-6 for such proposals to drift or the servoir. We form 9-331-6 for such proposals to drift or the servoir. Well and 100 form or such proposals to drift or the servoir. We form 9-331-6 for such proposals to drift or the servoir. We form 9-331-6 for such proposals to drift or the servoir. We form 9-331-6 for such proposals to drift or the servoir. We form 9-331-6 for such proposals to drift or the servoir. We form 9-331-6 for such proposals to drift or the servoir. We form 9-331-6 for such proposals to drift or the servoir. We form 9-331-6 for such proposals to drift or the servoir. We form 9-331-6 for such proposals to drift or the servoir. We form 9-331-6 for such proposals to drift or the servoir. We form 9-331-6 for such proposals to drift or the servoir. We form 9-331-6 for such proposals to drift or the servoir. We form 9-331-6 for such proposals to drift or the servoir. We form 9-331-6 for such proposals to drift or the servoir. We form 9-331-6 for such proposals to drift or the servoir. We form 9-331-6 for such proposals to drift or the servoir. We		5F-0/8405 & 5-
SUNDRY NOTICES AND REPORTS ON WELLS or not use this form for proposals to drill or to despen or plug back to a different to proposals. I coll ges KY other 2. NAME OF OPERATOR Tenneco 0i1 Company 3.Dores so of OPERATOR 720 S. Colo. Blvd., Denver, CO 80222 1. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) AT SUBFACE: 1120'FNL, 1570'FEL AT TOP PROD. INTERVAL: AT TOTAL DEPTH: C. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE. REPORT, OR OTHER DATA EQUEST FOR APPROVAL TO: ST WATER SHUT-OFF HOTO OR ACIDIZE HOTO OR AC		· [
Servoir, Use Form 9-330-C for such proposals. L. oil gas KY other L. oil Company L. ocolo Blvd., Denver, CO 80222 L. Ocation of Well (REPORT LOCATION CLEARLY. See space 17 below.) AT SUBFACE: 1120 FNL, 1570 FEL AT TOP ROD. INTERVAL: AT TOTAL DEPTH: C. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE. REPORT, OR OTHER DATA EQUEST FOR APPROVAL TO: SIT WATER SHUT-OFF LACTURE TREAT LOOT OR ACIDIZE PAIR WELL LIL OR ALTER CASING COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* DESCRIBE PROPOSED OR COMPLETED OPERATI	CULDRY NATION AND DEPORTS ON MELLS	
L. Oil Well Operator Tenneco Oil Company 8. ADDRESS OF OPERATOR 720 S. COIO. Blyd., Denver, CO 80222 1. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) 1. AT SURFACE: 1120 FNL, 1570 FEL AT TOP PROD. INTERVAL: AT TOTAL DEPTH: 1. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 12. COUNTY OF PARTSH 13. STATE San Juan New Mexico 14. APINO. 15. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 17. DESCRIBE FOR APPROVAL TO: BOX AND	·	
L. Oil gas well well other 2. NAME OF OPERATOR TENDECO 0il Company ADDRESS OF OPERATOR 720 S. Colo. Blvd., Denver, CO 80222 Basin Dakota 11. SEC., T. R. M. OR BLK. AND SURVEY OR AREA Sec. 1120 FNL, 1570 FEL AT TOP PROD. INTERVAL: AT TOTAL DEPTH: CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA CQUEST FOR APPROVAL TO: SI WATER SHUT-OF COMPLETE CONTROL TREAT COTO OR ACIDIZE FAIR WELL LLL OR ALTER CASING ULTIPLE COMPLETE CANDON* Report on Completion Operations 7. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 5/8-5/12/80 MIRUCU on 5/8/80. Perf'd Dakota @ 6656'-58, 6544-48, 6534-38, 6464-72, 6378-32, 6364-67 (110 shots) Acidized w/1000 gal 15% HCL and 100 balls; Frac'd in follow manner: 10000 gal foam pad, 33980# 20/40 sand. Landed 2 3/8" tubg @ 5972'. Released rig 5/12/80. Flowing to clean up.	(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	9 FADM OD I FÉOR SUBAR
Well Well Def other Zenneco Oil Company 5. ADDRESS OF OPERATOR T2O S. Colo. Blvd., Denver, CO 80222 5. LICATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below) AT SURFACE: 1120'FNL, 1570'FEL AT TOP PROD. INTERVAL: AT TOTAL DEFTH: 5. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA EQUEST FOR APPROVAL TO: SIT WATER SHUT-OFF TACTURE TREAT 1007 OR ACIDIZE 11. SEC. T., R. M., OR BLK. AND SURVEY OR AREA Sec. 14; 129N; R12N 12. CDUNTY OR PARTSH 13. STATE San Juan 14. API NO. 15. ELEVATIONS (SHOW DF, KDB, AND WD) 5811' 16. (NOTE: Report respires of multiple completion or zone change of form 8-330.) 7. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) 5/8-5/12/80 MIRUCU on 5/8/80. Perf'd Dakota @ 6656'-58, 6544-48, 6534-38, 6464-72, 6378-32, 6364-67 (110 shots) Acidized w/1000 gal 15% HCL and 100 bails: Frac'd in follow manner: 10000 gal foam pad, 33980# 20/40 sand. Landed 2 3/8" tubg @ 5972'. Released rig 5/12/80. Flowing to clean up.	A	
Z. NAME OF OPERATOR Tenneco 0il Company S. ANDRESS of OPERATOR 720 S. Colo. Blvd., Denver, CO 80222 S. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) AT SURFACE: 1120 'FNL, 1570 'FEL AT TOP PROD. INTERVAL: AT TOTAL DEPTH: S. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA EQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: SIT WATER SHUT-OFF ACTURE TREAT HOTO OR ACIDIZE PAIR WELL ULTIPLE COMPLETE HANGE ZONES BANDON* Repon't on Completion Operations 7. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) 5/8-5/12/80 MIRUCU on 5/8/80. Perf'd Dakota @ 6656'-58, 6544-48, 6534-38, 6464-72, 6378-32, 6364-67 (110 shots) Acidized w/1000 gal 15% HCL and 100 balls; Frac'd in follow manner: 10000 gal foam pad, 33980# 20/40 sand. Landed 2 3/8" tubg @ 5972'. Released rig 5/12/80. Flowing to clean up.		
Tenneco Oil Company 8. ADDRESS OF OPERATOR 720 S. Colo. Blvd., Denver, CO 80222 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below). AT SURFACE: 1120 'FNL, 1570 'FEL AT TOP PROD. INTERVAL: AT TOTAL DETH: 5. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA EQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: ST WATER SHUT-OFF HORD INTERVAL: HOOT OR ACIDIZE HORD HORD HORD HORD HORD HORD HORD HORD	2. NAME OF OPERATOR	
Basin Dakota 720 S. Colo. Blvd., Denver, CO 80222 3. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) AT SURFACE: 1120 FNL, 1570 FEL AT TOP PROD. INTERVAL: AT TOTAL DEPTH: 5. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA EQUEST FOR APPROPAL TO: SUBSEQUENT REPORT OF: ST WATER SHUT-OFF COMPLETE COMPLETE CHARGE ZORD. HOOT OR ACIDIZE CHARGE STREET COMPLETE CHARGE ZORD. LILIPILE COMPLETE CHARGE STREET COMPLETE CHARGE ZORD. 7. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) 5/8-5/12/80 MIRUCU on 5/8/80. Perf'd Dakota @ 6656'-58, 6544-48, 6534-38, 6464-72, 6378-32, 6364-67 (110 shots) Acidized w/1000 gal 15% HCL and 100 balls; Frac'd in follow manner: 10000 gal foam pad, 33980# 20/40 sand. Landed 2 3/8" tubg @ 5972'. Released rig 5/12/80. Flowing to clean up.		
3. COCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) AT SURFACE: 1120 'FNL, 1570 'FEL AT TOP PROD. INTERVAL: AT TOP PROD. INTERVAL: AT TOTAL DEPTH: 3. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 5. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 5. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 6. CHECK APPROPOVAL TO: 5. ST WATER SHUT-OFF 6. CHECK APPROPOVAL TO: 6. SET WATER SHUT-OFF 6. CHECK APPROPOVAL TO: 6. SELEVATIONS (SHOW DF, KDB, AND WD) 7. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) 7. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) 7. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) 7. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent of the work.) 7. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (
A. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) AT SURFACE: 1120 'FNL, 1570 'FEL AT TOP PROD. INTERVAL: AT TOTAL DEPTH: S. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA EQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: SIT WATER SHUT-OFF ACIDIZE CAPITY OR ACIDIZE COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 5/8-5/12/80 MIRUCU on 5/8/80. Perf'd Dakota @ 6656'-58, 6544-48, 6534-38, 6464-72, 6378-32, 6364-67 (110 shots) Acidized w/1000 gal 15% HCL and 100 balls. Frac'd in follow manner: 10000 gal foam pad, 33980# 20/40 sand. Landed 2 3/8" tubg @ 5972'. Released rig 5/12/80. Flowing to clean up.		
Delow) AT SURFACE: 1120 FNL, 1570 FEL AT TOP PROD. INTERVAL: AT TOTAL DEPTH: S. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA EQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: SUBSEQUENT REPORT OF: SUBSEQUENT REPORT OF: (NOTE: Report require of multiple completion or zone ULTIPLE COMPLETE HANGE ZONES BANDON* 7. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 5/8-5/12/80 MRUCU on 5/8/80. Perf'd Dakota @ 6656 -58, 6544-48, 6534-38, 6464-72, 6378-32, 6364-67 (110 shots) Acidized w/1000 gal 15% HCL and 100 balls; frac'd in follow manner: 10000 gal foam pad, 33980# 20/40 sand. Landed 2 3/8" tubb @ 5972'. Released rig 5/12/80. Flowing to clean up.		AREA
AT TOP PROD. INTERVAL: AT TOTAL DEPTH: S. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA EQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: ST WATER SHUT-OFF HOOT OR ACIDIZE EPAIR WELL ULL OR ALTER CASING HANDON* Report on Completion Operations 7. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent deteils, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 5/8-5/12/80 MIRUCU on 5/8/80. Perf'd Dakota @ 6656'-58, 6544-48, 6534-38, 6464-72, 6378-32, 6364-67 (110 shots) Acidized w/1000 gal 15% HCL and 100 balls. Frac'd in follow manner: 10000 gal foam pad, 33980# 20/40 sand. Landed 2 3/8" tubg @ 5972'. Released rig 5/12/80. Flowing to clean up.	helow)	Sec. 14; \$29N; R12W
AT TOTAL DEPTH: 5. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 14. API NO. 15. ELEVATIONS (6HOW DF, KDB, AND WD) 5811' 15. ELEVATIONS (6HOW DF, KDB, AND WD) 5811' 16. CHECK APPROPRIATE DATA 17. CHECK APPROPRIATE DATA 18. API NO. 19. API N		12. COUNTY OR PARISH 13. STATE
S. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA EQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: ST WATER SHUT-OFF	- · · · · · · - · - · - · · - · · - · · - ·	San Juan - New Mexico
EQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: ST WATER SHUT-OFF ACTURE TREAT HOOT OR ACIDIZE EPAIR WELL ULL OR ALTER CASING ULL TIPLE COMPLETE HANGE ZONES BANDON* ther) Report on Completion Operations 7. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 5/8-5/12/80 MIRUCU on 5/8/80. Perf'd Dakota @ 6656'-58, 6544-48, 6534-38, 6464-72, 6378-32, 6364-67 (110 shots) Acidized w/1000 gal 15% HCL and 100 balls. Frac'd in follow manner: 10000 gal foam pad, 33980# 20/40 sand. Landed 2 3/8" tubg @ 5972'. Released rig 5/12/80. Flowing to clean up.	AT TOTAL DEPTH:	14. API NO. 4841 8 981
EQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: SUBSEQUENT REPORT OF		
EQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: ST WATER SHUT-OFF CACTURE TREAT CHOOT OR ACIDIZE EPAIR WELL ULL OR ALTER CASING ULTIPLE COMPLETE Change on: Form 3-330.) ULTIPLE COMPLETE Change on: Form 3-330.) ILTIPLE COMPLETE Change on: Form 3-330.) T. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 5/8-5/12/80 MIRUCU on 5/8/80. Perf'd Dakota @ 6656'-58, 6544-48, 6534-38, 6464-72, 6378-32, 6364-67 (110 shots) Acidized w/1000 gal 15% HCL and 100 balls. Frac'd in follow manner: 10000 gal foam pad, 33980# 20/40 sand. Landed 2 3/8" tubg @ 5972'. Released rig 5/12/80. Flowing to clean up.	REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)
ST WATER SHUT-OFF CACTURE TREAT HOOT OR ACIDIZE PAIR WELL JLL OR ALTER CASING LITIPLE COMPLETE HANGE ZONES SANDON* ther) Report on Completion Operations 7. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 5/8-5/12/80 MIRUCU on 5/8/80. Perf'd Dakota @ 6656'-58, 6544-48, 6534-38, 6464-72, 6378-32, 6364-67 (110 shots) Acidized w/1000 gal 15% HCL and 100 balls; Frac'd in follow manner: 10000 gal foam pad, 33980# 20/40 sand. Landed 2 3/8" tubg @ 5972'. Released rig 5/12/80. Flowing to clean up.	FOUEST FOR ARREDOVAL TO. SUBSEQUENT PERCENT OF	5811' \$40 B B B B
CACTURE TREAT GOT OR ACIDIZE GOT OR	and the second s	
HOOT OR ACIDIZE EPAIR WELL ULT OR ALTER CASING ULTIPLE COMPLETE HANGE ZONES ASANDON* Report on Completion Operations 7. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 5/8-5/12/80 MIRUCU on 5/8/80. Perf'd Dakota @ 6656'-58, 6544-48, 6534-38, 6464-72, 6378-32, 6364-67 (110 shots) Acidized w/1000 gal 15% HCL and 100 balls. Frac'd in follow manner: 10000 gal foam pad, 33980# 20/40 sand. Landed 2 3/8" tubg @ 5972'. Released rig 5/12/80. Flowing to clean up.		
ULTIPLE COMPLETE		
ULTIPLE COMPLETE HANGE ZONES Date of the completion of the com		(NOTE: Report results of multiple completion or zone
HANGE ZONES BANDON* ther) Report on Completion Operations 7. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 5/8-5/12/80 MIRUCU on 5/8/80. Perf'd Dakota @ 6656'-58, 6544-48, 6534-38, 6464-72, 6378-32, 6364-67 (110 shots) Acidized w/1000 gal 15% HCL and 100 balls. Frac'd in follow manner: 10000 gal foam pad, 33980# 20/40 sand. Landed 2 3/8" tubg @ 5972'. Released rig 5/12/80. Flowing to clean up.		
ANDON* Report on Completion Operations 7. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 5/8-5/12/80 MIRUCU on 5/8/80. Perf'd Dakota @ 6656'-58, 6544-48, 6534-38, 6464-72, 6378-32, 6364-67 (110 shots) Acidized w/1000 gal 15% HCL and 100 balls. Frac'd in follow manner: 10000 gal foam pad, 33980# 20/40 sand. Landed 2 3/8" tubg @ 5972'. Released rig 5/12/80. Flowing to clean up.		
7. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 5/8-5/12/80 MIRUCU on 5/8/80. Perf'd Dakota @ 6656'-58, 6544-48, 6534-38, 6464-72, 6378-32, 6364-67 (110 shots) Acidized w/1000 gal 15% HCL and 100 balls. Frac'd in follow manner: 10000 gal foam pad, 33980# 20/40 sand. Landed 2 3/8" tubg @ 5972'. Released rig 5/12/80. Flowing to clean up.	RANDON+	
including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 5/8-5/12/80 MIRUCU on 5/8/80. Perf'd Dakota @ 6656'-58, 6544-48, 6534-38, 6464-72, 6378-32, 6364-67 (110 shots) Acidized w/1000 gal 15% HCL and 100 balls. Frac'd in follow manner: 10000 gal foam pad, 33980# 20/40 sand. Landed 2 3/8" tubg @ 5972'. Released rig 5/12/80. Flowing to clean up.	ther) Report on Completion Operations	이 그는 그리는 한 경험통한 그를 확인하는 사람이
including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 5/8-5/12/80 MIRUCU on 5/8/80. Perf'd Dakota @ 6656'-58, 6544-48, 6534-38, 6464-72, 6378-32, 6364-67 (110 shots) Acidized w/1000 gal 15% HCL and 100 balls. Frac'd in follow manner: 10000 gal foam pad, 33980# 20/40 sand. Landed 2 3/8" tubg @ 5972'. Released rig 5/12/80. Flowing to clean up.		- Para
measured and true vertical depths for all markers and zones pertinent to this work.)* 5/8-5/12/80 MIRUCU on 5/8/80. Perf'd Dakota @ 6656'-58, 6544-48, 6534-38, 6464-72, 6378-32, 6364-67 (110 shots) Acidized w/1000 gal 15% HCL and 100 balls. Frac'd in follow manner: 10000 gal foam pad, 33980# 20/40 sand. Landed 2 3/8" tubg @ 5972'. Released rig 5/12/80. Flowing to clean up.		
MIRUCU on 5/8/80. Perf'd Dakota @ 6656'-58, 6544-48, 6534-38, 6464-72, 6378-32, 6364-67 (110 shots) Acidized w/1000 gal 15% HCL and 100 balls. Frac'd in follow manner: 10000 gal foam pad, 33980# 20/40 sand. Landed 2 3/8" tubg @ 5972'. Released rig 5/12/80. Flowing to clean up. wbsurface Safety Valve: Manu. and Type B. I hereby pertify that the foregoing is true and correct	7. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state including estimated date of starting any proposed work. If well is d	te all pertinent details, and give pertinent dates,
MIRUCU on 5/8/80. Perf'd Dakota @ 6656'-58, 6544-48, 6534-38, 6464-72, 6378-32, 6364-67 (110 shots) Acidized w/1000 gal 15% HCL and 100 balls. Frac'd in follow manner: 10000 gal foam pad, 33980# 20/40 sand. Landed 2 3/8" tubg @ 5972'. Released rig 5/12/80. Flowing to clean up. wbsurface Safety Valve: Manu. and Type B. I hereby pertify that the foregoing is true and correct	including estimated date of starting any proposed work. If well is d	firectionally drilled give subsurface locations and
6364-67 (110 shots) Acidized w/1000 gal 15% HCL and 100 balls. Frac'd in follow manner: 10000 gal foam pad, 33980# 20/40 sand. Landed 2 3/8" tubg @ 5972'. Released rig 5/12/80. Flowing to clean up. wbsurface Safety Valve: Manu. and Type B. I hereby pertify that the foregoing is true and correct	including estimated date of starting any proposed work. If well is d measured and true vertical depths for all markers and zones pertiner	firectionally drilled give subsurface locations and
manner: 10000 gal foam pad, 33980# 20/40 sand. Landed 2 3/8" tubg @ 5972'. Released rig 5/12/80. Flowing to clean up. ubsurface Safety Valve: Manu. and Type B. I hereby pertify that the foregoing is true and correct	including estimated date of starting any proposed work. If well is d measured and true vertical depths for all markers and zones pertiner 5/8-5/12/80	directionally drilled, give subsurface locations and nt to this work.)*
Released rig 5/12/80. Flowing to clean up. who will be a set of the set of t	including estimated date of starting any proposed work. If well is d measured and true vertical depths for all markers and zones pertiner 5/8-5/12/80 MIRUCU on 5/8/80. Perf'd Dakota @ 6656'-58, 6	directionally drilled, give subsurface locations and nt to this work.)* 5544-48, 6534-38, 6464-72, 6378-32,
ubsurface Safety Valve: Manu. and Type B. I hereby pertify that the foregoing is true and correct	including estimated date of starting any proposed work. If well is d measured and true vertical depths for all markers and zones pertiner 5/8-5/12/80 MIRUCU on 5/8/80. Perf'd Dakota @ 6656'-58, 66364-67 (110 shots) Acidized w/1000 gal 15% H	irrectionally drilled, give subsurface locations and nt to this work.)* 5544-48, 6534-38, 6464-72, 6378-32, ICL and 100 balls; Frac'd in follow
8. I hereby pertify that the foregoing is true and correct	including estimated date of starting any proposed work. If well is d measured and true vertical depths for all markers and zones pertiner 5/8-5/12/80 MIRUCU on 5/8/80. Perf'd Dakota @ 6656'-58, 6 6364-67 (110 shots) Acidized w/1000 gal 15% H manner: 10000 gal foam pad, 33980# 20/40 sand	irrectionally drilled, give subsurface locations and nt to this work.)* 5544-48, 6534-38, 6464-72, 6378-32, ICL and 100 balls; Frac'd in follow
3. I hereby pertify that the foregoing is true and correct	including estimated date of starting any proposed work. If well is d measured and true vertical depths for all markers and zones pertiner 5/8-5/12/80 MIRUCU on 5/8/80. Perf'd Dakota @ 6656'-58, 66364-67 (110 shots) Acidized w/1000 gal 15% H manner: 10000 gal foam pad, 33980# 20/40 sand	irrectionally drilled, give subsurface locations and nt to this work.)* 5544-48, 6534-38, 6464-72, 6378-32, ICL and 100 balls; Frac'd in follow
8. I hereby pertify that the foregoing is true and correct	including estimated date of starting any proposed work. If well is d measured and true vertical depths for all markers and zones pertiner 5/8-5/12/80 MIRUCU on 5/8/80. Perf'd Dakota @ 6656'-58, 6 6364-67 (110 shots) Acidized w/1000 gal 15% H manner: 10000 gal foam pad, 33980# 20/40 sand	irrectionally drilled, give subsurface locations and nt to this work.)* 5544-48, 6534-38, 6464-72, 6378-32, ICL and 100 balls; Frac'd in follow
8. I hereby pertify that the foregoing is true and correct	including estimated date of starting any proposed work. If well is d measured and true vertical depths for all markers and zones pertiner 5/8-5/12/80 MIRUCU on 5/8/80. Perf'd Dakota @ 6656'-58, 6 6364-67 (110 shots) Acidized w/1000 gal 15% H manner: 10000 gal foam pad, 33980# 20/40 sand	irrectionally drilled, give subsurface locations and nt to this work.)* 5544-48, 6534-38, 6464-72, 6378-32, ICL and 100 balls; Frac'd in follow
3. I hereby pertify that the foregoing is true and correct	including estimated date of starting any proposed work. If well is d measured and true vertical depths for all markers and zones pertiner 5/8-5/12/80 MIRUCU on 5/8/80. Perf'd Dakota @ 6656'-58, 66364-67 (110 shots) Acidized w/1000 gal 15% H manner: 10000 gal foam pad, 33980# 20/40 sand	irrectionally drilled, give subsurface locations and nt to this work.)* 5544-48, 6534-38, 6464-72, 6378-32, ICL and 100 balls; Frac'd in follow
8. I hereby pertify that the foregoing is true and correct	including estimated date of starting any proposed work. If well is d measured and true vertical depths for all markers and zones pertiner 5/8-5/12/80 MIRUCU on 5/8/80. Perf'd Dakota @ 6656'-58, 6 6364-67 (110 shots) Acidized w/1000 gal 15% H manner: 10000 gal foam pad, 33980# 20/40 sand	irrectionally drilled, give subsurface locations and nt to this work.)* 5544-48, 6534-38, 6464-72, 6378-32, ICL and 100 balls. Frac'd in follow
8. I hereby pertify that the foregoing is true and correct	including estimated date of starting any proposed work. If well is d measured and true vertical depths for all markers and zones pertiner 5/8-5/12/80 MIRUCU on 5/8/80. Perf'd Dakota @ 6656'-58, 6 6364-67 (110 shots) Acidized w/1000 gal 15% H manner: 10000 gal foam pad, 33980# 20/40 sand	irrectionally drilled, give subsurface locations and nt to this work.)* 5544-48, 6534-38, 6464-72, 6378-32, ICL and 100 balls. Frac'd in follow
3. I hereby pertify that the foregoing is true and correct	including estimated date of starting any proposed work. If well is d measured and true vertical depths for all markers and zones pertiner 5/8-5/12/80 MIRUCU on 5/8/80. Perf'd Dakota @ 6656'-58, 66364-67 (110 shots) Acidized w/1000 gal 15% H manner: 10000 gal foam pad, 33980# 20/40 sand	irrectionally drilled, give subsurface locations and nt to this work.)* 5544-48, 6534-38, 6464-72, 6378-32, ICL and 100 balls. Frac'd in follow
	including estimated date of starting any proposed work. If well is d measured and true vertical depths for all markers and zones pertiner 5/8-5/12/80 MIRUCU on 5/8/80. Perf'd Dakota @ 6656'-58, 66364-67 (110 shots) Acidized w/1000 gal 15% H manner: 10000 gal foam pad, 33980# 20/40 sand	irrectionally drilled, give subsurface locations and nt to this work.)* 5544-48, 6534-38, 6464-72, 6378-32, ICL and 100 balls. Frac'd in follow
	including estimated date of starting any proposed work. If well is different measured and true vertical depths for all markers and zones pertiner 5/8-5/12/80 MIRUCU on 5/8/80. Perf'd Dakota @ 6656'-58, 66364-67 (110 shots) Acidized w/1000 gal 15% H manner: 10000 gal foam pad, 33980# 20/40 sand Released rig 5/12/80. Flowing to clean up.	irrectionally drilled, give subsurface locations and nt to this work.)* 5544-48, 6534-38, 6464-72, 6378-32, ICL and 100 balls. Frac'd in follow
IGNED WILL MANUEL Admin. Supervisor 2 5/27/80	including estimated date of starting any proposed work. If well is d measured and true vertical depths for all markers and zones pertiner 5/8-5/12/80 MIRUCU on 5/8/80. Perf'd Dakota @ 6656'-58, 6 6364-67 (110 shots) Acidized w/1000 gal 15% H manner: 10000 gal foam pad, 33980# 20/40 sand Released rig 5/12/80. Flowing to clean up.	irrectionally drilled, give subsurface locations and nt to this work.)* 5544-48, 6534-38, 6464-72, 6378-32, ICL and 100 balls. Frac'd in follow
	including estimated date of starting any proposed work. If well is different measured and true vertical depths for all markers and zones pertiner 5/8-5/12/80 MIRUCU on 5/8/80. Perf'd Dakota @ 6656'-58, 6 6364-67 (110 shots) Acidized w/1000 gal 15% H manner: 10000 gal foam pad, 33980# 20/40 sand Released rig 5/12/80. Flowing to clean up.	firectionally drilled, give subsurface locations and not to this work.)* 5544-48, 6534-38, 6464-72, 6378-32, ICL and 100 balls; Frac'd in follow 1. Landed 2 3/8" tubg @ 5972'.
(This appear for Endaged on Onder office was)	including estimated date of starting any proposed work. If well is different measured and true vertical depths for all markers and zones pertiner 5/8-5/12/80 MIRUCU on 5/8/80. Perf'd Dakota @ 6656'-58, 6 6364-67 (110 shots) Acidized w/1000 gal 15% H manner: 10000 gal foam pad, 33980# 20/40 sand Released rig 5/12/80. Flowing to clean up.	firectionally drilled, give subsurface locations and not to this work.)* 5544-48, 6534-38, 6464-72, 6378-32, ICL and 100 balls; Frac'd in follow 1. Landed 2 3/8" tubg @ 5972'.
/ virius sipace for rederal or state office use) विशेष विशेष विशेष विशेष	including estimated date of starting any proposed work. If well is display measured and true vertical depths for all markers and zones pertiner 5/8-5/12/80 MIRUCU on 5/8/80. Perf'd Dakota @ 6656'-58, 6 6364-67 (110 shots) Acidized w/1000 gal 15% H manner: 10000 gal foam pad, 33980# 20/40 sand Released rig 5/12/80. Flowing to clean up. B. I hereby pertify that the foregoing is true and correct agreed to the foregoing is true and correct agreed. Admin. Super	Sirectionally drilled, give subsurface locations and not to this work.)* 5544-48, 6534-38, 6464-72, 6378-32, ICL and 100 balls: Frac'd in follow 1. Landed 2 3/8" tuby @ 5972'. Sirectionally drilled, give subsurface locations and not to this work.)* Frac'd in follow 1. Landed 2 3/8" tuby @ 5972'. Sirectionally drilled, give subsurface locations and not to this work.)* Frac'd in follow 1. Landed 2 3/8" tuby @ 5972'.
PPROVED BY TITLE DATE	including estimated date of starting any proposed work. If well is different measured and true vertical depths for all markers and zones pertiner 5/8-5/12/80 MIRUCU on 5/8/80. Perf'd Dakota @ 6656'-58, 6 6364-67 (110 shots) Acidized w/1000 gal 15% H manner: 10000 gal foam pad, 33980# 20/40 sand Released rig 5/12/80. Flowing to clean up.	Sirectionally drilled, give subsurface locations and not to this work.)* 5544-48, 6534-38, 6464-72, 6378-32, ICL and 100 balls: Frac'd in follow 1. Landed 2 3/8" tuby @ 5972'. Sirectionally drilled, give subsurface locations and not to this work.)* Frac'd in follow 1. Landed 2 3/8" tuby @ 5972'. Sirectionally drilled, give subsurface locations and not to this work.)* Frac'd in follow 1. Landed 2 3/8" tuby @ 5972'.
JNDITIONS OF APPROVAL, IF ANY: SEE THE PROVAL OF APPROVAL OF APPR	including estimated date of starting any proposed work. If well is d measured and true vertical depths for all markers and zones pertiner 5/8-5/12/80 MIRUCU on 5/8/80. Perf'd Dakota @ 6656'-58, 6 6364-67 (110 shots) Acidized w/1000 gal 15% H manner: 10000 gal foam pad, 33980# 20/40 sand Released rig 5/12/80. Flowing to clean up. B. I hereby pertify that the foregoing is true and correct argued to the foregoing is true and correct of the foregoing is	firectionally drilled, give subsurface locations and not to this work.)* 5544-48, 6534-38, 6464-72, 6378-32, ICL and 100 balls. Frac'd in follow 1. Landed 2 3/8" tubg @ 5972'. SVISOr DATE SVISOR DATE Trice use)
NMOCC BETARE BETARE	including estimated date of starting any proposed work. If well is d measured and true vertical depths for all markers and zones pertiner 5/8-5/12/80 MIRUCU on 5/8/80. Perf'd Dakota @ 6656'-58, 6 6364-67 (110 shots) Acidized w/1000 gal 15% H manner: 10000 gal foam pad, 33980# 20/40 sand Released rig 5/12/80. Flowing to clean up. B. I hereby pertify that the foregoing is true and correct argued to the foregoing is true and correct of the foregoing is	firectionally drilled, give subsurface locations and not to this work.)* 5544-48, 6534-38, 6464-72, 6378-32, ICL and 100 balls. Frac'd in follow 1. Landed 2 3/8" tubg @ 5972'. SVISOr DATE SVISOR DATE Trice use)
NAME NAME OF THE PROPERTY OF T	including estimated date of starting any proposed work. If well is discussived and true vertical depths for all markers and zones pertiner 5/8-5/12/80 MIRUCU on 5/8/80. Perf'd Dakota @ 6656'-58, 6 6364-67 (110 shots) Acidized w/1000 gal 15% H manner: 10000 gal foam pad, 33980# 20/40 sand Released rig 5/12/80. Flowing to clean up. B. I hereby pertify that the foregoing is true and correct admin. Super Title Admin. Super Title This space for Federal or State office of the percentage of the per	firectionally drilled, give subsurface locations and not to this work.)* 5544-48, 6534-38, 6464-72, 6378-32, ICL and 100 balls. Frac'd in follow 1. Landed 2 3/8" tubg @ 5972'. SVISOr DATE SVISOR DATE Trice use)

*See Instructions on Reverse Side