

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other

2. NAME OF OPERATOR

Tenneco Oil Company

3. ADDRESS OF OPERATOR

720 S. Colo. Blvd., Denver, CO 80222

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

825'FNL, 1660'FWL, Unit C

AT SURFACE:

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON* ☐

(other) Report on Completion Operations

SUBSEQUENT REPORT OF

RECEIVED

JUN 3 1980

U.S. GEOLOGICAL SURVEY

WATER DIVISION

5. LEASE

SF-080245

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Hamner

9. WELL NO.

2A

10. FIELD OR WILDCAT NAME

Dakota/Mesa Verde

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 28; T29N; R9W

12. COUNTY OR PARISH

13. STATE

San Juan

New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

5721'

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

5 / 9-5/25/80

MIRUCU on 5/9/80. Circ hole w/1% KCL. Perf'd Dakota w/2 SPF @ 6514-18, 6538-44, 6582-96, 6631-33, 6641-48, 6656-74. Acidized Dakota w/2000 gal 15% HCL & 151 ball sealers. Frac'd w/80000 gal 30# XL gel, 80000# 20/40 sand. Set Model F packer @ 6475'. Press. tested packer to 3000#-held. Perf'd Mesa Verde w/2SPF @ 4193-95, 4211-18, 4244-48, 4306-12, 4318-30, 4412-33(104 holes). Acidized w/ 2000 gal mud acid & 156 balls. Frac'd Mesa Verde w/156000# 20/40 sand & 143000 gal KCL slick water. Perf'd Mesa Verde w/2SPF @ 3870-80, 4059-64, 4077-86, 4091-95(56 holes). Acidized w/1000 gal 15% HCL & 42 balls. Frac'd w/80000# 20/40 sand 86/84 gel KCL slick water. Landed long string in packer(6475). Landed short string opened @ 4211'. RDMOCU on 5/25/80. Flowing to clean up.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

Carly J. Hatten

TITLE

Admin. Supervisor

DATE

5/30/80

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

ACCEPTED FOR RECORD

JUN 3 1980

EARMINGTON DISTRICT