J 15 29N 11W

STATE OF NEW MEXICO
ENERGY and MINERALS DEPARTMENT

Location of Well: J152911 Page 1

OIL CONSERVATION DIVISION
NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

Operator: AMOCO PRODUCTION COMPANY Lease/Well #:COOPER GC 1E/~~HARE G1~~
Meter #:94104 RTU:1-211-01 County:SAN JUAN

	NAME RESERVOIR OR POOL	TYPE PROD	METHOD PROD	MEDIUM PROD
UPR COMP	COOPER GC 1E/HARE G1 OCH 94104	gas	flwg.	
LWR COMP	COOPER GC 1E DK 94108	gas	flwg.	

PRE-FLOW SHUT-IN PRESSURE DATA

	Hour/Date Shut-In	Length of Time Shut-In	SI Press. PSIG	Stabilzed
UPR COMP	06/10/91	72 Hours	387	yes
LWR COMP	06/10/91	72 Hours	509	yes

FLOW TEST DATE NO.1

Commenced at (hour,date)* Zone Producing (Upr/Lwr)

TIME (hour, date)	LAPSED TIME SINCE*	PRESSURE Upper	PRESSURE Lower	Prod Temp.	REMARKS
06/10/91	Day 1	263	396		Both Zones SI
06/11/91	Day 2	313	463		Both Zones SI
06/12/91	Day 3	387	509		Both Zones SI
06/13/91	Day 4	265	521		Both Zones SI
06/14/91	Day 5	243	539		upper zone Flow
06/15/91	Day 6	240	539		upper zone Flow

Production rate during test
Oil:_____ BOPD based on _____ BBLs in _____ Hrs _____ Grav___ GOR ___
Gas: _____ MFCPD:Tested theu (Orifice or Meter):METER

MID-TEST SHUT-IN PRESSURE DATA

	Hour,Date SI	Length of Time SI	SI Press. PSIG	Stabilized (yes/no)
UPR COMP				
LWR COMP				

RECEIVED
AUG 30 1991
OIL CON. DIV.
DIST. 3

(Continue on reverse side)

Commenced at (Hour, date) **				Zone producing (Upper or Lower)	
TIME (Hour, date)	LAPSED TIME SINCE **	PRESSURE		PROD. ZONE TEMP.	REMARKS
		Upper Completion	Lower Completion		

Production rate during test

Oil: _____ BOPD based on _____ Bbls. in _____ Hours. _____ Grav. _____ GOR _____

Gas: _____ MCFPD: Tested thru (Orifice or Meter): _____

Remarks: _____

I hereby certify that the information herein contained is true and complete to the best of my knowledge.

Approved AUG 3 0 1991 19___
New Mexico Oil Conservation Division

By Original Signed by CHARLES GHOLSON

Title DEPUTY OIL & GAS INSPECTOR, DIST. #3

Operator AMOCO PRODUCTION CO.

By D Dallas

Title FIELD TEST CO-ORDINATOR

Date 8/22/91

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such test shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.

2. At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.

3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.

4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such zone shall be maintained for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: If, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.

5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.

6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.

7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the flow hour thereafter, and immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the same time) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tests: all pressures, throughout the entire test, shall be measured and recorded with recording pressure gauges the accuracy of which is to be checked at least twice, once at the beginning and once at the end of each test, with deadweight pressure gauges. If a well is a gas-oil or an oil-gas dual completion, the deadweight pressure gauge need be required on the oil zone only, with recording pressure gauges to be used on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form C-104, revised 10-01-78, with all deadweight pressures indicated thereon as well as the flowing temperature (gas zones only) and gravity and GOR (oil zones only).