

N. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-55

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>		7. Unit Agreement Name Gallegos Canyon Unit
2. Name of Operator Amoco Production Company		8. Farm or Lease Name
3. Address of Operator 501 Airport Drive Farmington, New Mexico 87401		9. Well No. 93E
4. Location of Well UNIT LETTER <u>L</u> <u>1725</u> FEET FROM THE <u>South</u> LINE AND <u>590</u> FEET FROM THE <u>West</u> LINE, SECTION <u>36</u> TOWNSHIP <u>29N</u> RANGE <u>12W</u> NMPM.		10. Field and Pool, or Wildcat Basin Dakota
15. Elevation (Show whether DF, RT, GR, etc.) 5397' GL		12. County San Juan


16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	Completion <input checked="" type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Completion operations commenced on 6-30-80. Total depth of the well is 6110', and plug back depth is 6060'. Perforated intervals from 5920' to 5962' with 2 spf, a total of 84, .38" holes. Perforated interval from 5848' to 5870' with 2 spf, a total of 44, .38" holes. Foam fraced with 29,838 gallons of frac fluid, 55,000 gal foam, and 114,880# of 20-40 sand.

Landed 2-3/8" tubing at 6017'. Swabbed the well and released the rig on 7-28-80



18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED _____ TITLE Administrative Supervisor DATE 7-28-80

APPROVED BY Original Signed by FRANK T. CHAVEZ TITLE SUPERVISOR DISTRICT #3 DATE JUL 31 1980

CONDITIONS OF APPROVAL, IF ANY: