

COPIES RECEIVED	4
CONTRIBUTION	
SANTA FE	1
LAND OFFICE	
OPERATOR	2

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

SUNDRY NOTICES AND REPORTS ON WELLS

DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input checked="" type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER	5a. Indicate Type of Lease State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>
2. Name of Operator S & I Oil Company	5. State Oil & Gas Lease No.
3. Address of Operator 413 W. Main St. , Farmington, New Mexico 87401	7. Unit Agreement Name
4. Location of Well UNIT LETTER I , 1840 FEET FROM THE South LINE AND 520 FEET FROM East LINE, SECTION 11 TOWNSHIP 29N RANGE 15W NMPM.	8. Farm or Lease Name Dorothy
15. Elevation (Show whether DF, RT, GR, etc.) 5179 GR	9. Well No. 1
	10. Field and Pool, or Wildcat Cha Cha Gallup
	12. County San Juan

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☒
CASING TEST AND CEMENT JOB ☐
OTHER ☐
ALTERING CASING ☐
PLUG AND ABANDONMENT ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

4/25/80 Spud Well
4/26/80 T. D. 305' ran 7 Joints 8 5/8" 23.0 lb., ERW casing(289.52) set at 298' with 250 sacks Class "B" cement with 3% Calcium Chloride and 1/4 lb. Celloflake per sack. Cement circulated approximately 2 1/2 barrels. Pressure test with 1000 psig. Test ok.

5/6/80 T.D. 4670'. Ran 148 joints 4-1/2", 10.50 K-55 casing (4720.07') set at 4665' with:
First stage: 300 sacks 50-50 Pozmix with 6-1/4 lbs. D-24 1/4 lbs. D-29 and 10% Salt (down). Calculated top of cement 3500'.

Second Stage: 575 sacks 65-35 Pozmix (12% Gel) with 6-1/4 lbs. D-24 (Gilsonite) per sack, followed by 100 sacks 50-50 Pozmix, 2% Gel with 6-1/4 lbs. D-24 (Gilsonite) with 10% Salt. Stage Collar at 3120'. Circulated approximately 50 barrels.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Troy R. Strickland TITLE Managing Partner DATE 5/13/80

APPROVED BY Original Signed by FRANK T. CHAVEZ

TITLE SUPERVISOR DISTRICT # 3

DATE MAY 14 1980

CONDITIONS OF APPROVAL, IF ANY: