

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐
well well

2. NAME OF OPERATOR
Tenneco Oil Company

3. ADDRESS OF OPERATOR
720 S. Colo. Blvd., Denver, CO 80222

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
820'FNL, 1550'FWL
AT SURFACE:
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF	<input type="checkbox"/>	<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>	<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>	<input type="checkbox"/>
(other)	Report on Drilling Operations	

5. LEASE
SF-065557

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Cornell E

9. WELL NO.
1E

10. FIELD OR WILDCAT NAME
Basin Dakota

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 12; T29N; R12W

12. COUNTY OR PARISH
San Juan

13. STATE
New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
5817'GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

5/12-5/22/80
Spudded 12½" hole 12:15PM, 5/12/80. Drilled to 343' and ran 8 jts of 9 5/8", 36# csg & set @ 342'. Cmt w/250 sxs CL B 2% CACL2. Circ to surface. Reduced hole 7 7/8" and drilled to TD of 6617' on 5/20/80. Ran 208 jts of 4½, 10.5# csg & set @ 6609'. Cmt 1st stage w/400 sxs 65/35 Pozmix and followed w/150 sxs CL B neat. Open DV tool and circulated. Cmt second stage w/1350 sxs lite. Circ to surface. Released rig 5/22/80. WOCU.

Subsurface Safety Valve: Manu. and Type

18. I hereby certify that the foregoing is true and correct.

SIGNED Charles Martin TITLE Asst. Div. Admin. Manager DATE June 12, 1980

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL _____

ACCEPTED FOR RECORD

JUN 19 1980

BY E. G. [Signature]
FARMINGTON DISTRICT

*See Instructions on Reverse Side

ACCEPTED FOR RECORD

JUN 14 1980

