

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well ☐ other & water injection well2. NAME OF OPERATOR
Energy Reserves Group, Inc.3. ADDRESS OF OPERATOR
P.O. Box 3280 - Casper, Wyoming 826024. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 2,015' FSL & 830' FEL (NE/SE)
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) Well History ☒

SUBSEQUENT REPORT OF:

<input type="checkbox"/>	RECEIVED
<input type="checkbox"/>	APR 27 1980
<input type="checkbox"/>	U. S. GEOLOGICAL SURVEY
<input type="checkbox"/>	FARMINGTON, N. M.

5. LEASE SF-080723
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME Gallegos Canyon Unit
8. FARM OR LEASE NAME
9. WELL NO. 306
10. FIELD OR WILDCAT NAME Undersigned Fruitland & Mesaverd
11. SEC., T., R., M. OR BLK. AND SURVEY OR AREA Sec. 19-T29N-R12W
12. COUNTY OR PARISH San Juan
13. STATE New Mexico
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD) GRD 5,415' KB 5,429'

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Drilled 8-3/4" hole to 4,154' and ran logs.

Ran 107 jts. 7" O.D., 23# & 20#, K-55, 8Rth, SS-, LT&C & ST&C, R-3, new casing set @ 4,154' (K.B) w/DV tool @ 1,605'.

Cemented 1st stage w/690 sx. of 50-50 Pozmix w/2% Gel & 1/4# Fluoropolymer
Cemented 2nd stage w/470 sx. of 50-50 Pozmix w/2% Gel & 1/4# Fluoropolymer
down @ 11:30 P.M. 4-23-80. Good cement returns.

4-24-80: W.O.C.T. & R.D.R.T.

Subsurface Safety Valve: Manu. and Type _____

Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Ron C. Gillette TITLE Drilling Supt.-RMD DATE April 24, 1980

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

NMOC

*See Instructions on Reverse Side