

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

# NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	
7. Unit Agreement Name	
8. Farm or Lease Name	
KIRTLAND #5	
9. Well No.	
10. Field and Pool, or Willcat	
CHA CHA GALLUP	
12. County	
SAN JUAN	

## SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>
2. Name of Operator
CARIBOU FOUR CORNERS, INC.
3. Address of Operator
Rm 219, TRANSWESTERN BLDG. 404 N 31ST STREET BILLINGS, MONT. 59101
4. Location of Well
UNIT LETTER J, 2030 FEET FROM THE SOUTH LINE AND 2060 FEET FROM THE EAST LINE, SECTION 12 TOWNSHIP 29 N RANGE 15 W NMPM.
15. Elevation (Show whether DF, RT, GR, etc.)

16.

## Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

### NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐  
TEMPORARILY ABANDON ☐  
PULL OR ALTER CASING ☐  
OTHER ☐


PLUG AND ABANDON ☐  
CHANGE PLANS ☐  
OTHER ☐

### SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐  
COMMENCE DRILLING OPNS. ☒  
CASING TEST AND CEMENT JOBS ☐  
OTHER ☐  
ALTERING CASING ☐  
PLUG AND ABANDONMENT ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

5/19/80 Spud 12 noon with cable tool  
5/26/80 TD 344' with cable tool.  
5/27/80 Set 337.39' of 8 5/8" 23# casing with Texas style shoe and baffle plate. Set @ 339 GL with 275 sacks regular cement, 1/4# flow seal per sack, 3% CaCl<sub>2</sub>. Plug down 3:45 p.m. Cement within 15 ft. of surface, packed surface casing with gravel.  
9/25/80 Drilled out from surface with 7 7/8" bit @ 6:30 a.m. with rotary tools.  
9/30/80 TD 4700'  
10/1/80 Ran 123 jts. of 9.5# and 10.5# 4 1/2" casing set @ 4700.14 KB with 875 sacks cement in two stages.



18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Denny G. Foust TITLE Geologist DATE 11-07-80

APPROVED BY Original Signed by FRANK T. CHAVEZ SUPERVISOR DISTRICT 3 DATE NOV 17 1980  
CONDITIONS OF APPROVAL, IF ANY: