

STATE OF NEW MEXICO  
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

OIL CONSERVATION DIVISION  
P. O. BOX 2088  
SANTA FE, NEW MEXICO 87501

Form C-103  
Revised 10-1-78

5a. Indicate Type of Lease  
State  Fee

5. State Oil & Gas Lease No.  
**E-6516**

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input type="checkbox"/> OIL WELL <input checked="" type="checkbox"/> GAS WELL OTHER-	7. Unit Agreement Name
2. Name of Operator <b>TEXACO Inc. Attention: G. L. Eaton</b>	8. Farm or Lease Name <b>Keys Com.</b>
3. Address of Operator <b>P. O. Box 2100, Denver, Colorado 80201</b>	9. Well No. <b>1E</b>
4. Location of Well UNIT LETTER <b>F</b> <b>1750</b> FEET FROM THE <b>North</b> LINE AND <b>1770</b> FEET FROM THE <b>West</b> LINE, SECTION <b>32</b> TOWNSHIP <b>29N</b> RANGE <b>10W</b> NMPM.	10. Field and Pool, or Wildcat <b>Basin Dakota</b>
15. Elevation (Show whether DF, RT, GR, etc.) <b>5680' CR 5692' KB</b>	12. County <b>San Juan</b>

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>
OTHER <input type="checkbox"/>	OTHER <u>Run Surface Casing</u> <input checked="" type="checkbox"/>
PLUG AND ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
CHANGE PLANS <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Strudded well 7:30 PM. 8-13-80.

Ran 587' of 8-5/8" OD 2 1/4# casing. Set at 582' and cemented with 405 sacks Class "B" cement with 2% CaCl<sub>2</sub> and 1/4# Flo-seal per sack. Cement circulated to surface. Plug down at 3:00 AM, 8-15-80.

Pressured casing to 1300# for 30 minutes. Held ok.



18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED SIGNED: G. L. EATON TITLE District Superintendent DATE Sept. 5, 1980

APPROVED BY Original Signed by FRANK T. CHAVEZ TITLE SUPERVISOR DISTRICT # 3 DATE SEP 10 1980

CONDITIONS OF APPROVAL, IF ANY:  
0000 (2) SEP 20M (2)