

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	
E-6516	

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input type="checkbox"/> OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER-	7. Unit Agreement Name
2. Name of Operator TEXACO Inc. Attention: G. L. Eaton	8. Farm or Lease Name Keys Com.
3. Address of Operator P. O. Box 2100, Denver, Colorado 80201	9. Well No. 1E
4. Location of Well UNIT LETTER F , 1750 FEET FROM THE North LINE AND 1770 FEET FROM THE West LINE, SECTION 32 TOWNSHIP 29N RANGE 10W NMPM.	10. Field and Pool, or Wildcat Basin Dakota
15. Elevation (Show whether DF, RT, GR, etc.) 5692' KB	12. County San Juan

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐
OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOB ☐
OTHER Run Production Casing ☒
ALTERING CASING ☐
PLUG AND ABANDONMENT ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Ran 6532' (166 joints) of 4-1/2" OD 10.5# ST&C casing. DV Tool at 3386' KB.
Set casing at 6520' KB. Cemented first stage with 950 sacks Class "A" 50-50
pozmix. Plug down at 11:00 PM, 8-31-80. Dropped bomb tool open and started
circulating. Good circulation, no lost circulation. Plug held.
Cemented second stage with 890 sacks HOWCO Lite and 150 sacks Class "B" 50-50
pozmix. Pumped 450 psig. Did not lose circulation. No cement returns to
surface. Plug down at 8:40 AM, 9-1-80. Rig released at 2:00 PM, 9-1-80.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED: G. L. EATON

TITLE District Superintendent

DATE Sept. 15, 1980

Original Signed by FRANK T. CHAVEZ

APPROVED BY

TITLE

SUPERVISOR DISTRICT #3

DATE

SEP 18 1980

CONDITIONS OF APPROVAL, IF ANY: