STATE OF NEW MEXICO ENERGY and MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

This form is not to be used for reporting

DIST.

is	In Southeast New Mexico NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST								
		<i>~</i> ,	Pati Pau		10110	"A"	Well 2-E		
Operator	Uni	O-Teps	vp. 29 N	The Lease I	1.1	Count	Jan Juan		
of Well: U	Init <u>E</u>	_ Sec. <u>_34</u> T	wp. <u>29 /V</u>	Rge. ZZ	2	METHOD OF PROD.	PROD. MEDIUM		
		NAME OF RESERVOIR		TYPE OF PROD. METHOD OF PRO (Oll or Goe) (Flow or Art. Little		(Flow or Art. LIII)	(Tbg. or Ceg.)		
Upper Completion	Ma	llub		Oil		umping	Casing		
Lower Completion	DA	beta		Jos	}	Tubing			
L		70 1090	PRE-FLO	W SHUT-IN PRI	ESSURE DA	ITA U	<u> </u>		
Upper	tour, date shu	11th 9:00 A.1		in S	i press. psig 23	/	Stabilized? (Yes or No)		
Completion	9//0/ Hour, date shu	/ <u>8 8</u>	Length of time shulp		il press. psig	_	Stabilized? (Yes or No)		
Lower Completion	2/19	188	17mo	the !	52	<u>. 7</u>	/// 0		
	•			FLOW TEST N			14444		
Convenced	el (hour, date	1 9/13/8	8 9:00 A. PRESS	. <u>m</u> .		ng (Upper or Lowert (COPPLE		
	TIME LAPSED TIME		Upper Completion	Lower Completion	PROD. ZON TEMP.		REMARKS		
9/00		1 day	179	528					
900	A.M.	2 days	214	528					
9:00	A.M. 188	3 days	23/_	529					
900	A, M.	4 days	90	529	59	0	<u></u>		
9/15	188	5 days	_ 88	529	590				
	• : ==	1							
Producti	ion tate d	uring test							
Floduca	ion 12.0 G	P.O.D	D based on	Bbls. ir	1	Hours.	Grav GOR		
Oil:		BOP	D 025tu 00		رم: ۲۰۰	Marar): (M	eter		
Gas:						Meter):			
				EST SHUT-IN P		ATA	Stabilized? (Yes or No)		
Hour, date shut-in Length of time shut			nut-in	SI press. psig					
Complete			:				Stabilized? (Yes or No)		

FLOW TEST NO. 2

Commenced at (hour, date) **				Zone producing (Upper or Lower):			
TIME	LAPSED TIME	PRESSURE Upper Completion Lower Completion		PROD. ZONE	REMARKS .		
				1	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		
				•			
·-					**************************************		
roduction rate d	during test			<u> </u>	<u> </u>		
Oil:	ВОР	D based on	Bbls. in	Hours.	Grav GOR		
Gas:		мсі	PD: Tested thru	(Orifice or Meter	·):		
				<u> </u>	-		
				<u>.</u>			
hereby certify d	hat the informati	on herein contain			of my knowledge.		
New Mexico O	il Conservation I	Division	_ 17	perator <u>Lazza.</u>	on Texas Petroleum in Marman Luction Technicia		
0	riginal Signed by	CHARLES GROLSON	l B	by partia	a Marman		
Зу			Т	Title Prop	luction Technician		
lide <u>D</u> l	EPUTY OIL & GAS	INSPECTOR, DIST.	#3	Date 9/20	9/88		

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever temedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- 2. At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure trabilization. Both zones shall remain shut-in until the well-head pressure in each has trabilized, provided however, that they need not remain shut-in more than were days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the aumosphere due to the lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- 6 Flow Ten'No. 2 shall be conducted even though no leak was indicated during Flow Ten No. 1. Provedure for Flow Ten No. 2 is to be the same as for Flow Ten No. 1 except

that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.

7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tents: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be thetched at least rwice, once at the beginning and once at the end of each test, with a decadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described term shall be filed in triplicate within 15 days after completion of the test, Term shall be filed with the Azter District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).

Job separation sheet

STATE OF NEW MEXICO ENERGY and MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

Page 1 Revised 10/01/78

This form is not to be used for reporting packer leakage tests in Southeast New Mexico

NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

Operator Un	ion Texa	· Petrolei	un_ Lease	Pier	<u>دی</u>	<u>"A" </u>	Well AE		
ocation of Well: Unit				10 W		County	San Jus	<u>~</u>	
	NAME OF RESERVOIR OR POOL			OD. •)	METHOD OF PROD. (Flow or Arl Lift)		PROD. MEDIUM (Tbg. or Geg.)		
Upper Completion	llup		ail		Pu	mping	ng Casing		
Lower Completion					70	swing	Tubing		
			W SHUT-IN PI	SI press. psig	DATA	Stab	Hilzed? (Yes or No)		
Upper Completion: // 4	1/89	M Length of time shut	<u> </u>		223		Hilzed? (Yes, or No)		
Lower Completion // 4	núi in 8:30 A. N 1/89	1 3 day	2		<u>520</u>		No		
		0	FLOW TEST				0		
Consmenced at (hour, dat	11/7/89	8:30 A.n press		Zone prod	ucing (Uppe	r or Lowert	: love		
TIME (hour, date)	LAPSED TIME SINCE*	Upper Completion	Lower Completion	PROD. Z	i i		REMARKS		
8:30 A·M. 11/5/89	1 day	211	438						
8:30 Am.	2 days	220	512			· · · · · · · · · · · · · · · · · · ·			
9:30 A.M. 11/7/89	3 days	223	<u>520</u>						
8:30 A.M. 11/8/89	4 days	242	358	5	40				
8:30 A.M. 11/9/89	5 days	_ 249	495	54	10			.	
Production rate d	J		nt to '		House	Grav	, GOI		
Oil:	BOP	D based on	Bbls. in		_ Hours.				
Gas:		MCF	PD; Tested thru	(Orifice o	or Meter)	: med			
		MID-TE	ST SHUT-IN P	RESSURE	DATA		Allered 2 Mag at Not		
Upper Hour, date	shut-in	Length of time shu	ıt-in	Si press. psy			bilized? (Yes or No)	<u></u>	
Completion:			//	St press, paig			Stabilized (res or No)		
							DEG <u>1</u> 5198	9	

OIL CONI. DIV. DIST. 3

FLOW TEST NO. 2

		Zone producing (Upper or Lowert						
TIME	LAPSED TIME	PRESSURE		PROD. ZONE		· · · · · · · · · · · · · · · · · · ·		
(hour, date)	SINCE **	Upper Completion	Lower Completion	TEMP.	RE	MARKS -		
					r	and the second		
· ·			1					
								
					:			
					<u>:</u>			
						·		
oduction rate d		D based on	Bbls in	Hours	Grav	GOP		
):			
,								
pproved	DEC 15	<u> 1989 </u>			t of my knowledge.	s Leterleus		
		CHARLES GHOLOON		Sala ic Prop	•	Inalyst.		
ide0	EPUTY OIL & GAS	INSPECTOR, DIST.		ic 12//	2/89			

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever temedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.

Commenced at (hour, date) ##

- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Ten No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- 3. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- 6. Flow Test'No. 2 shall be conducted even though no leak was indicated during Flow Ten No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except

that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.

7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tesu: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Parker Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).