UNITED STATES DEPARTMENT OF THE INTERIOR

	Form Approved. Budget Bureau No. 42–R1424
	5. LEASE 0470 VO 13 SF 070402 B
	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
ent	7. UNIT AGREEMENT NAME
	8. FARM OR LEASE NAME Eaton Com B
	9. WELL NO. #1
	10. FIELD OR WILDCAT NAME Blanco Mesaverde
17	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
	Sec.25; T29N; R11W 12. COUNTY OR PARISH 13. STATE San Juan New Mexico
 DE,	14. API NO.
,	15. ELEVATIONS (SHOW DF, KDB, AND WD) 5562 gr.
NIFD	
CEIVED \	
(NOTE Report results of multiple completed area change on Form 9–330	
CON POR	
state all pertinent details, and give pertinent dates, is directionally drilled, give substrace focations and tinent to this work.)*	
o 270'. Ran 6 jts 9 5/8" 36# csg. Circ. cmt to surface. Reduced hole jts (4560') 7" 23# csg. set at lite tail in w/150sx CL-B. PD on Cmt 2nd stage w/375 sx 65/35 POZ	
SU	rface. Release rig 8/20/80. d out DV. Tagged cmt at 4475.

GEOLOGICAL SURVEY SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a difference or use Form 9–331–C for such proposals.) well other well 2. NAME OF OPERATOR Tenneco Oil Company 3. ADDRESS OF OPERATOR 720 So.Colo.Blvd., Denver CO 80222 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 10401 below.) AT SURFACE: 890 FSL 790' FEL AT TOP PROD. INTERVAL: AT TOTAL DEPTH: 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTIC REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL PULL OR ALTER CASING MULTIPLE COMPLETE CHANGE ZONES ABANDON* (other) Spudding/csq. report 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly including estimated date of starting any proposed work. If well measured and true vertical depths for all markers and zones per 8/14/80 Spudded 13 3/4" hole 8/14/80. Drilled t set @ 269' Cmt w/200 sx CL-B & 2% CACL2. to 8 3/4" drilled to TD at 4550'. Ran 113 4550 w/ DV at 3110. Cmt 1st stage w/85 sx 8/20/80. Open DV & Circ. No cmt. circ. mix 6% gel. Tail w/150 sx CL-B. No cmt to MIRUSU RIH 2 7/8"tbg. w/bit & scraper. Dri Drilled out PBTD. Set @ _ Subsurface Safety Valve: Manu. and Type 18. I hereby certify that the foregoing is true and correct Div. Admin. Manager DATE September 24, 1980 ے TITLE کے (This space for Federal or State office use) DATE TITLE APPROVED BY CONDITIONS OF APPROVAL & ASSO

STON DISTAICT *See Instructions on Reverse Side