

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

OIL CONSERVATION DIVISION

P.O. Box 2088

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

Santa Fe, New Mexico 87504-2088

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

WELL API NO.

3004524431

5. Indicate Type of Lease

STATE ☒

FEE ☐

6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL
WELL ☐

GAS
WELL ☒

OTHER

2. Name of Operator

Amoco Production Company

Attention:

Gail M. Jefferson

3. Address of Operator

P.O. Box 800

Denver

Colorado

80201

(303) 830-6157

8. Well No.

1

9. Pool name or Wildcat

Blanco MV/Bimfd Chacra

4. Well Location

Unit Letter

C

: 990

Feet From The

North

Line and

1650

Feet From The

West

Line

Section

19

Township

29N

Range

10W

NMPM

San Juan

County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☒

CASING TEST AND CEMENT JOB ☐

OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

MIRUSU 6/24/96. TOH w/ 1-1/4" tubing, pull on 2-3/8", seal assembly stuck, cut off tubing, fish out seal assembly and tail pipe.

TIH w/tbg to 4341'. Pumped 280 sxs Class B cmt from 3,381' to 4341'. TIH w/tbg and retainer, set cement retainer at 2845'. Pumped 21 sxs Class B cmt below retainer. Sting out and spot 17 sxs Class B on top of retainer at 2795'. Spot a cmt plug inside casing from 910' to 1,480' w/81 sxs Class B cmt. Spot cmt plug from surface to 778' w/227 sxs Class B cmt.

Cut off wellhead and top off casing strings. Install marker.

RDMOSU 6/29/96.

RECEIVED
JUL 23 1996

OIL CON. DIV.
DIST. 3

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

Gail M. Jefferson

TITLE

Sr. Admin. Staff Asst.

DATE 07-22-1996

TYPE OR PRINT NAME

Gail M. Jefferson

TELEPHONE NO. (303) 830-6157

(This space for State Use)

APPROVED BY

[Signature]

TITLE

N.M.O.C.D. (Deputy
P&G Inspector)

DATE

7-31-96

CONDITIONS OF APPROVAL, IF ANY: