

FEB 27 '97 04:40PM AMOCO 12TH FLOOR 3838384777 P.1

AMOCO

Date 2/27 Time Sent 4:45

This transmission consists of 5 pages

Notes:

AMOCO

FAX Number

FAX Operator's Number for Confirmation

AMOCO

FAX Telephone Number

Voice Telephone Number

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-85

3a. Indicate Type of Lease State ☐ Fee ☐	
5. State Oil & Gas Lease No. NM 494	
7. Unit Agreement Name	
8. Form or Lease Name Sullivan Frame Com B	
9. Well No. 1	
10. Field and Pool, or Wildcat Mesaverde/Chacra	
12. County San Juan	

DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO RE-DRILL OR PLUG BACK TO A DIFFERENT RESERVOIR. USE APPLICATION FOR PERMIT - (FORM C-101) FOR SUCH PROPOSALS.

1. OIL ☐ GAS ☒ OTHER ☐

2. Name of Operator
Tenneco Oil Company

3. Address of Operator
P.O. Box 3249, Englewood, CO 80155

4. Location of Well
 UNIT LETTER D 1175 FEET FROM THE N LINE AND 880' FEET FROM THE W 30 LINE, SECTION 30 TOWNSHIP 29N RANGE 10W N.M.P.M.

15. Elevation (Show whether DP, RT, CR, etc.)

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK ☐ TEMPORARILY ABANDON ☐ PULL OR ALTER CASING ☐ OTHER ☐	PLUG AND ABANDON ☐ CUSHION PLANS ☐ OTHER ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1703.

10/14/80
 Killed Mesaverde. RIH w/tbg. to 4440. POOH w/tbg. RIH w/model "D" pkr set @ 2990. Dump 2 sx sand on "D" pkr w/expendable plug. Filled hole w/2% KCL. PT to 3000 PSI. Held ok. Perf'd Chacra. (20SPF): 2702-10, 2795-2803. RIH w/full bore pkr to 2765'. Spot 250 gals. 15% HCL in annulus. Set pkr. Acidized down tbg. w/250 gals 15% HCL & 24 balls. RIH to knock balls off perfs. POOH to 2577'. PT pkr OK. Frac'd Chacra down tbg. w/70% quality foam, 80,000# 20/40 sand. Total foam 80,000 gals. AIR: 20 BPM @ 2500 PSI. ISIP 1450 PSI. 15 mins. SIP: 1400 PSI. Killed Chacra w/2% KCL water. POOH & laid down 2 7/8" tbg. RIH w/2 3/8" beveled tbg. muleshoe; seal assy, & blast joints. Tagged sand @ 2930'. Clean out w/foam to pkr @ 2990'.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Sullivan J. Kugler TITLE Asst. Div. Admin. Mrg. DATE 12/5/80
 SUPERVISOR DISTRICT 3
 APPROVED BY Original Signed by FRANK T. CHAVEZ TITLE _____ DATE DEC 1980
 CONDITIONS OF APPROVAL, IF ANY: _____

RECEIVED
 FEB 28 1997
 OIL CON. DIV.
 DIST. 3