

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐

2. NAME OF OPERATOR  
Koch Exploration Co (Div of Koch Ind., Inc.)

3. ADDRESS OF OPERATOR  
P.O. Box 2256; Wichita, Kansas 67201

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 1850' FWL & 930' FNL ( NE NW)  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF	<input type="checkbox"/>		<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>		<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>		<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>		<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>		<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>		<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>		<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>		<input type="checkbox"/>
(other) Run Intermediate Casing			

5. LEASE  
NM-010468

6. IF INDIAN, ALLOTTEE OR TRIBE NAME  
N/A

7. UNIT AGREEMENT NAME  
N/A

8. FARM OR LEASE NAME  
Howell

9. WELL NO.  
E-1

10. FIELD OR WILDCAT NAME  
Basin Dakota

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec. 3-30N-8W


12. COUNTY OR PARISH  
San Juan

13. STATE  
NM

14. API NO.  
N/A


15. ELEVATIONS (SHOW DF, KDB, AND WD)  
GR 6222', KB 6236', DF 6235;

(NOTE: Report results of multiple completion or zone change on Form 9-330.)



17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Drilled 8-3/4" hole to 3250'. Ran 80 jts 7" 20 & 26# K-55 LT&C new casing. Set casing @ 3248'. Cmtd w/375 sx 50-50 Poz w/2% Gel & 1/4# flocele & 100 sx class "B" w/1/4# celoflake and 2% CaCl. Cement circulated. Plug down at 8:45 A.M. 8-24-80.



Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Donald L. Schmitt TITLE Operations Manager DATE August 26, 1980

(This space for Federal or State office use)

APPROVED BY ACCEPTED FOR RECORD  
CONDITIONS OF APPROVAL, IF ANY:

TITLE \_\_\_\_\_ DATE \_\_\_\_\_

SEP 02 1980

FARMINGTON DISTRICT  
BY BW

\*See Instructions on Reverse Side

NMOCC