(other) Spud and Casing Report

PULL OR ALTER CASING MULTIPLE COMPLETE CHANGE ZONES ABANDON\*

## **UNITED STATES** DEPARTMENT OF THE INTERIOR **GEOLOGICAL SURVEY**

Dec. 1973	Budget Bureau No. 42-R1424
UNITED STATES	5. LEASE
DEPARTMENT OF THE INTERIOR	NM-01772A
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS  (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	7. UNIT AGREEMENT NAME
reservoir. Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME
1. oil gas X other	Reid "A"
well well X other	9. WELL NO.
2. NAME OF OPERATOR	1-M
Southland Royalty Company	10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR	Basin Dakota/Blanco Mesa Verde
P.O. Drawer 570, Farmington, N.M. 87401	11. SEC., T., R., M., OR BLK. AND SURVEY OR
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	AREA
below.)	Section 13, T29N, R10W
AT SURFACE: 1510' FSL & 2390' FEL	12. COUNTY OR PARISH 13. STATE
AT TOP PROD. INTERVAL: AT TOTAL DEPTH:	San Juan New Mexico
	14. API NO.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	5668' GR
TEST WATER SHUT-OFF	
SHOOT OR ACIDIZE	
REPAIR WELL	(NOTE: Report results of multiple completion or zone
PULL OR ALTER CASING	f = f(x)
CHANGE ZONES	r i

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Spudded 13-3/4" surface hole at 2:15 P.M. 12-26-80 and drilled to a 12/26/80 Ran 6 joints (219.56') of 10-3/4", 32.75#, K-55 Total Depth of 242'. casing set at 232'. Cemented with 140 sacks of Class "B" with 1/4# flocele per sack and 3% CaCl2. Plug down at 9:45 P.M. 12-26-80. Cement circulated to surface.

	JAN O CO.
Subsurface Safety Valve: Manu. and Type	Set @H CON CO
18. I hereby certify that the foregoing is true and correct	DOT. 3
SIGNED Cither Declark Dilling Clerk DATE	December 29, 1980
ACCEPTED FUK RECUMU (This space for Federal or State office use)	
APPROVED BY DATE DATE	

FARMINGTON DISTRICT