

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other

2. NAME OF OPERATOR

Southland Royalty Company

3. ADDRESS OF OPERATOR

P.O. Drawer 570, Farmington, NM 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1510' FSL & 2390' FEL

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐

SUBSEQUENT REPORT OF:

(other) Casing Report

☐
☐
☐
☐
☐
☐
☐
☐
☒

5. LEASE

NM-01772A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Reid "A"

9. WELL NO.

1-M

10. FIELD OR WILDCAT NAME

Basin Dakota/Blanco Mesaverde

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Section 13, T29N, R10W

12. COUNTY OR PARISH

San Juan

13. STATE

New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
5668' GR

(NOTE: Report results of multiple completion or zone change on Form 9-331-C.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

12/29/80 Ran 56 joints (2280.40') of 7-5/8", 26.40#, K-55 casing set at 2272'. Cemented with 284 sacks of Class "B" 50/50 Poz with 6% gel, followed with 90 sacks of Class "B" and 2% CaCl₂. Plug down at 5:45 P.M. 12-29-80. Top of Cement at 600'.
1/03/81 Ran 114 joints (4531.19') of 5-1/2", 15.5#, K-55 casing set from 2141' to 6673'. Cementd with 433 sacks of Class "B" 50/50 Poz with 1/4# gel flake per sack and 6% gel. Plug down at 7:45 A.M. 1-3-81.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Robert J. [Signature] TITLE Drilling Clerk DATE Jan 5, 1981

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

FARMINGTON DISTRICT