

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other ☐
2. NAME OF OPERATOR
SUPRON ENERGY CORPORATION
3. ADDRESS OF OPERATOR
P.O. Box 808, Farmington, New Mexico 87401
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: *1120 ft./S ; 1120 ft./W line*
AT TOP PROD. INTERVAL: *Same as above*
AT TOTAL DEPTH: *Same as above*

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF ☐ ☐
FRACTURE TREAT ☐ ☐
SHOOT OR ACIDIZE ☐ ☐
REPAIR WELL ☐ ☐
PULL OR ALTER CASING ☐ ☐
MULTIPLE COMPLETE ☐ ☐
CHANGE ZONES ☐ ☐
ABANDON* ☐ ☐
(other) *Ran 2-7/8" tubing as casing string*

5. LEASE
SF 080724-A
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME
Zachry
9. WELL NO.
23
10. FIELD OR WILDCAT NAME
Bloomfield Chacra Extension
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 34, T-29N, R-10W, N.M.P.M.
12. COUNTY OR PARISH
San Juan
13. STATE
New Mexico
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
5718 R.K.B.

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

- 1. Drilled 6-3/4" hole w/mud to total depth of 3070 ft. R.K.B. Reached total depth on 12-26-80.*
- 2. Ran 97 jts. of 2-7/8", E.U.E., 6.50# tubing as a casing string. Landed at 3055 ft. R.K.B. w/float collar at 3045 ft. R.K.B.*
- 3. Cemented with 330 sacks of 65-35-6 w/12 1/2 lb. of Gilsonite per sack and 200 sacks of 50-50 POZ mix w/1/4 lb. of cello-flakes per sack. Plug down at 4:45 p.m. 12-29-80.*
- 4. Cement circulated to surface.*

Subsurface Safety Valve: Manu. and Type _____

Set @ _____

18. I hereby certify that the foregoing is true and correct

SIGNED *Kenneth E. Roddy* TITLE *Production Supt.* DATE *December 31, 1980*
Kenneth E. Roddy

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL _____

TITLE _____ DATE _____

JAN 07 1981

FARMINGTON DISTRICT

*See Instructions on Reverse Side

NM000

