

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved.

Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM-014378

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Texaco
H. Loe - Federal "B"

9. WELL NO.

2E

10. FIELD AND POOL, OR WILDCAT

Basin Dakota

11. SEC., T., R., M., OR ELEM. AND
SURVEY OR AREA

Sec. 23 T29N-R12W

12. COUNTY OR PARISH

San Juan

13. STATE

New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)1. ☐ OIL
WELL ☐ GAS
WELL ☒ OTHER

2. NAME OF OPERATOR

Texaco Inc.

Attention: G. L. Eaton

3. ADDRESS OF OPERATOR

P. O. Box 2100, Denver, Colorado 80201

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surfaceSW $\frac{1}{4}$ NW $\frac{1}{4}$ Sec. 23

1700' FNL & 1050' FWL, Sec. 23

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

5657' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☐REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐Ran Surface Casing ☒(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-
nent to this work.) *

Spudded well at 1:15 AM, 10-18-80.

Ran 565' (13 joints) of 8-5/8" OD 24# K-55 ST&C casing. Landed at 501' KB
and cemented with 450 sacks Class "B" cement with 2% CaCl. Good returns.
Circulated cement to surface. Bumped plug at 12:10 PM, 10-19-80. Float held.

18. I hereby certify that the foregoing is true and correct

SIGNED: G. L. EATON TITLE: District Superintendent DATE: Nov. 6, 1980

(This space for Federal or State office use)

APPROVED BY: SIGNED: G. L. EATON TITLE: DATE:

CONDITIONS OF APPROVAL, IF ANY:

USGS (5) OCCC (2) GLE FARM (2) DIST
Farmington Aztec BY: BWA

*See Instructions on Reverse Side

710000