

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other ☐  
2. NAME OF OPERATOR  
SUPRON ENERGY CORPORATION  
3. ADDRESS OF OPERATOR  
P.O. Box 808, Farmington, New Mexico 87401  
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 1020 ft./S ; 1120 ft./W line  
AT TOP PROD. INTERVAL: Same as above  
AT TOTAL DEPTH: Same as above

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF	<input type="checkbox"/>		<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>		<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>		<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>		<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>		<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>		<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>		<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>		<input type="checkbox"/>

(other) Ran 2-7/8" tubing as casing string

5. LEASE  
NM 0702  
6. IF INDIAN, ALLOTTEE OR TRIBE NAME  
  
7. UNIT AGREEMENT NAME  
  
8. FARM OR LEASE NAME  
Reid "B"  
9. WELL NO.  
3  
10. FIELD OR WILDCAT NAME  
Bloomfield Chacra Ext.  
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec. 31, T-29N, R-10W, N.M.P.M.  
12. COUNTY OR PARISH  
San Juan  
13. STATE  
New Mexico  
14. API NO.  
  
15. ELEVATIONS (SHOW DF, KDB, AND WD)  
5752 R.K.B.

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

1. Drilled 6-5/8" hole with mud to total depth of 3100 ft. R.K.B. Total depth was reached on 3-11-81.
2. Ran 99 joints of 2-7/8" E.U.E., 6.50# tubing as the casing string. Landed at 3095 ft. R.K.B. with float collar at 3064 ft. R.K.B.
3. Cemented with 350 sacks of 65-35-12 with 12 1/2 lb. of gilsonite per sack and 200 sacks of 50-50 POZ mix with 2% gel and 10% salt. Plug down at 11:30 a.m. 3-12-81.
4. Circulated 10 bbls. of cement slurry to the surface.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Kenneth E. Roddy TITLE Production Supt. DATE March 16, 1981  
(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

\*See Instructions on Reverse Side

ACCEPTED FOR RECORD

MAR 24 1981

FARMINGTON DISTRICT