

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease
State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. B-11318

SUNDRY NOTICES AND REPORTS ON WELLS <small>(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)</small>		
1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name Gallegos Canyon Unit	
2. Name of Operator Energy Reserves Group, Inc.	8. Farm or Lease Name	
3. Address of Operator P.O. Box 3280 - Casper, Wyoming 82602	9. Well No. 323	
4. Location of Well UNIT LETTER <u>M</u> , <u>1030</u> FEET FROM THE <u>South</u> LINE AND <u>860</u> FEET FROM THE <u>West</u> LINE, SECTION <u>32</u> TOWNSHIP <u>29N</u> RANGE <u>12W</u> NMPM.	10. Field and Pool, or Wildcat West Kutz Pictured Cliffs	
15. Elevation (Show whether DF, RT, GR, etc.) G.L. 5,622' - K.B. 5,624'	12. County San Juan	

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	Well History <input checked="" type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

The above referenced well was spudded @ 3:00 AM 3-14-81.

Drilled 9-7/8" hole to 125'. Ran 3 jts 7" O.D., 17#, H-40, R-3, ST&C new casing set @ 125'. Cemented w/65 sx of Class "B" cement w/2% CaCl₂ & 1/4# Celloflake/sx. Plug down @ 6:45 AM 3-14-81. Good cement returns.

Nippled up and pressure tested BOPE to 500 psi--held o.k.

Drilled 6-1/4" hole to 1,630' and ran logs.

Ran 40 jts 4-1/2" O.D., 10.5#, K-55, R-3, ST&C new casing set @ 1,622'. Cemented w/200 sx of 50-50 Pozmix w/2% Gel & 1/4# Flocele/sx & 0.5% CFR-2. Plug down @ 5:30 PM 3-16-81. Good cement returns.

M.O.R.T. & W.O.C.T.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Rose C. Billings TITLE Drlg Supt - RMD DATE 3-17-81

Original Signed by FRANK T. CHAVEZ
APPROVED BY _____ TITLE SUPERVISOR OF OIL & GAS DATE MAR 22 1981
CONDITIONS OF APPROVAL, IF ANY: