

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other2. NAME OF OPERATOR
Energy Reserves Group, Inc.3. ADDRESS OF OPERATOR
P.O. Box 3280 - Casper, Wyoming 826024. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1,790' FNL & 1,165' FEL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐☒
☐
☐
☐
☐
☐
☐
☐5. LEASE
SF-078109

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME
Gallegos Canyon Unit

8. FARM OR LEASE NAME

9. WELL NO.
32210. FIELD OR WILDCAT NAME
West Kutz Pictured Cliffs11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 31-T29N-R12W12. COUNTY OR PARISH
San Juan13. STATE
New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
G.L. 5,543' - K.B. 5,545'

(NOTE: Report results of well tests, completion, or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

The above referenced well was spudded @ 3:30 am 2-16-81.

Drilled 9-7/8" hole to 125'. Ran 3 jts 7" O.D., 17#, R-3 new casing set @ 124' w/50 sx of Class "B" cement w/2% CaCl₂ & 1/4# Flocele/sx. Plug down @ 9:30 am 2-16-81. Good cement returns. Pressure tested BOPE to 500 psi - held o.k.

Drilled 6-1/4" hole to 1,651' and ran logs.

Ran 4-1/2" O.D., 10.5#, K-55, R-3, ST&C new casing set @ 1,643'. Cemented w/250 sx of 50-50 Pozmix w/2% Gel & 1/4# Flocele/sx & 0.6% CFR-2. Plug down @ 9:30 am 2-22-81. Good cement returns.

Subsurface Safety Valve: Manu. and Type

Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED James C. Billigin TITLE Drig Supt-RMD DATE 2-23-81

(This space for Federal or State office use)

ACCEPTED FOR RECORD

TITLE

DATE

MAR 8 1981

FARMINGTON DISTRICT

BY Casper