

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

**SUNDRY NOTICES AND REPORTS ON WELLS**

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other ☐  
2. NAME OF OPERATOR  
Tenneco Oil Company  
3. ADDRESS OF OPERATOR  
P. O. Box 3249, Englewood, CO 80155  
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 1585' FSL 1535' FWL "J"  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:


TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐

SUBSEQUENT REPORT OF:

(other) Fish tbg, run in hole w/new string

RECEIVED

(NOTE: Report results of multiple completions or change on Form 9-330.)



5. LEASE  
SF-080245  
6. IF INDIAN, ALLOTTEE OR TRIBE NAME  
7. UNIT AGREEMENT NAME  
8. FARM OR LEASE NAME  
Hamner  
9. WELL NO.  
2E  
10. FIELD OR WILDCAT NAME  
Basin Dakota  
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec. 28, T29N R3W  
12. COUNTY OR PARISH  
San Juan  
13. STATE  
New Mexico  
14. API NO.  
15. ELEVATIONS (SHOW DF, KDB, AND WD)  
5818' gr.

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*:

5/10/81 - RIH w/tbg spear would not go in tbg. RIH w/tbg and overshot, overshot too large POOH w/overshot. RIH w/tbg and tapered tap unable to tap into tbg. POOH w/tbg and tap.

5/11/81 - RIH w/tbg and impression block. POOH w/same. Block showed open collar facing up. RIH w/tbg, standard centralizer and tap. Tapped into tbg fish. POOH w/tbg and tbg fish.

5/13/81 - RIH w.tbg, drill collars. POOH w/same. Laid down. Unload new string of tbg. RIH w/tbg, bit sub and 3-7/8" bit. Drilled to bridge plug. Pushed bottom slips to PBTD @ 6754', POOH w/tbg and bit subs.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Asst. Div. Adm. Mgr. TITLE Asst. Div. Adm. Mgr. DATE 5/19/81

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE ASST. DIV. ADM. MGR.  
CONDITIONS OF APPROVAL, IF ANY:

NMOCC

\*See Instructions on Reverse Side

MAY 28 1981

6-23