UNITED STATES

_	Budget Bureau No. 42-R142	2.
5. LEASE		

	DEPARTMENT OF THE INTERIOR	SF 080724 A			
	GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTE	E OR TRIBE NAME		
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)		7. UNIT AGREEMENT NAME			
reservoir. U	se Form 9-331-C for such proposals.)	8. FARM OR LEASE NAI	ME		
1. oil well	gas well other	Zachry 9. WELL NO.			
2. NAME	OF OPERATOR	27			
	PRON ENERGY CORPORATION	10. FIFED OR WILDCAT	NAME +		
	ESS OF OPERATOR				
P.C	Box 808, Farmington, New Mexico 87401	11. SEC., T., R., M., OR	BLK. AND SURVEY OR		
4. LOCA	TION OF WELL (REPORT LOCATION CLEARLY. See space 17	AREA	O TOUT AT M TO M		
below	(.)	Sec. 34, T-29N, R-10W, N.M.P.M. 12. COUNTY OR PARISH 13. STATE			
AT SU	URFACE: 1715 ft./N ; 790 ft./E line OP PROD. INTERVAL: Same as above		New Mexico		
AT TOTAL DEPTH: Same as above		14. API NO.			
16 CHEC	K APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	14. AIT NO.			
	RT, OR OTHER DATA	15. ELEVATIONS (SHOW	V DE KDR AND WD)		
,,_, ,	,	5607 R.K.B.			
REQUEST	FOR APPROVAL TO: SUBSEQUENT REPORT OF:				
FRACTUR					
REPAIR W	VELL 🔲 🗎	(NOTE: Report results of m change on Form 9	cultiple completion or zone 1991		
	ALIEN COOK	change on Form 9	-330.1 A A A A A A A A A A A A A A A A A A A		
MULTIPLE CHANGE			00/ 1981		
ABANDON	ι• Π Π υ. s. GEΩ	LOGICAL SAMALA	Dies COM		
(other)	Ran 2-7/8" tubing as casing string FAMEL	KCTOR, N. M.	3"		
بدياه سا	CRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly stated ding estimated date of starting any proposed work. If well is discreted and true vertical depths for all markers and zones pertinents.	irectionally drilled, give sunt to this work.)*	bsurface locations and		
1.	 Drilled 6-5/8" hole with mud to total depth of 3040 ft. R.K.B. Total depth was reached on 3-22-81. 				
2.	Ran 98 joints of 2-7/8" E.U.E., 6.50# tu R.K.B. with float collar at 3009 ft. R.K		040 ft.		
3.	Cemented with 320 sacks of 65-35-12 with per sack, 100 sacks of 50-50 POZ mix wit 5:30 a.m. 3-23-81.				
4.	Cement circulated to the surface.				
	ce Safety Valve: Manu. and Typeeby. certify that the foregoing is true and correct				
SIGNED A	Fineth E. Roddy (This space for Federal or State of	pt. DATE March 2	1, 1981		
	(This space for Federal or State of	fice use)			
APPROVED	*IT: F				
CONDITION	NS OF APPROVAL, IF ANY:				
		ľ	ICCEPTED FOR RECORD		

MAR 26 1981