Page 1

OIL CONSERVATION DIVISION NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

Opera Me	tor: AMOCO ter #:93958	PRODUCTION	COMP RTU:	ANY Leas 0-000-00	e/Well #:HA C	AMNE Coun	R 003E ty:SAN 0	NAUT	
	NAME RESER	TYPE PROD!	E PROD! METHOD PRO		DD MEDIUM PROD				
UPR COMP	HAMNER 0031	01+		09		ng againg across states states across			
LWR COMP	HAMNER 003	Gas	Gas 09						
					PRESSURE DA				·
	Hour/Date	Shut-In !	hut-In Length of Ti		e Shut-In S		SI Press. PS		Stabilzed
UPR COMP	08/03/92				THE COLOR AND SHEET COLOR COLOR AND COLOR COLOR	1			
COMP	08703792 		***************************************						}
				FLOW TEST	DATE NO.1				
Comme	enced at (ho	our,date)*		ny paone amin'ny faritr'i Paritr'i Ariest Adult Adult (1879). Mandri			Zone P	roduci	ng (Upr We
(ho	TIME	LAPSED SINCE*	1 2.1 (1.44		RESSURE Lower		Prod Temp.		
08/03/92		Day 1		196	195	· .	.		h Zones SI
08/04/92		Day 1	3	538	37 <i>3</i>	3		hyZones SI 	
08/05/92		Day	5	545	380		1	Bot 	h Zones SI
08/06/92		Day	4	545	388	<u> </u>			
08/07/92		Day		555	185		!	\ \	
08/08/92		Day 		1. <u>1.80</u>	170	·		! ! !	n time wheel hade been reddy while hear while hade down
Oil:	uction rate	BOPD	based MFCP	D: lested	BBLs in theu (Orifi IN PRESSURE		C31 1 (C= c- /m)	Gra F):METE	v GOR ER
					•				and Committee
UPR COMF	{	1	gth o		(SI Press	5. F		E 6	ed (yes/no
EWR COMP								OCTA S	
	i		(Cc	ntinue on	reverse s	ide	, U	It Cor	

FLOW TEST NO. 2

Zone producing (Upper or Lower):

TIME	LAPSED TIME	PRES	SURE	PROD. ZONE	REMARKS		
(hour, date)	SINCE **	Upper Completion	Lower Completion	TEMP.			
			-: ·				
			e e e e e e e e e e e e e e e e e e e		·		
	- 1						
				-			
duction rate	during test	Comment of the Commen			· · · · · · · · · · · · · · · · · · ·		
	ВОР	D based on	Bbls. in	Hours.	Grav GOR		
s:	·	мсғ	PD: Tested thru	(Orifice or Meter):		
nereby certify	that the informati	ion herein contain	ed is true and co	mplete to the bes	st of my knowledge.		
		1992					
_	() at 13	IJUL.					
pproved	Oct 13	3:-:	19 (Operator	Imoco Broductes		
pproved New Mexico (Oct 1 3 Dil Conservation I	Division	19 (Operator	moco Broductes		
proved New Mexico (Oct 13 Dil Conservation I	Division	19	Operator	emses Broductes san 11/00 As ield Dech		

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

 A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.

reneed at frout, date) **

- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shur-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shart-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shot-in, in accordance with Paragraph 3 above.
- 6. Flow Text'No. 2 shall be considered even though no leak was indicated during Flow Text No. 1. Procedure for Flow Text No. 2 is to be the same as for Flow Text No. 1 except

- that the previously produced zone shall remain shast-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests; immediately prior to the beginning of each flow-period, at fifteen-minuse intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone texts: all pressures, throughout the entire text, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least rovice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Astee District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil 20-ses only).