5. LEASE

UNITED STATES DEPARTMENT OF THE INTERIOR

DEPARTMENT OF THE INTERIOR	14-20-603-5024
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
	Navajo
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)	7. UNIT AGREEMENT NAME
reservoir. Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME
1. oil gas cher	Navajo G
Well Street	9. WELL NO.
2. NAME OF OPERATOR	5
J. Gregory Merrion & Robert L. Bayless 3. ADDRESS OF OPERATOR	10. FIELD OR WILDCAT NAME Undes. Gallup
P. O. Box 1541, Farmington, NM 87401	11. SEC., T., R., M., OR BLK. AND SURVEY OR
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	AREA
below.)	Section 30, T29N, R17W
AT SURFACE: 990 FSL & 330 FEL AT TOP PROD. INTERVAL: same	12. COUNTY OR PARISH 13. STATE
AT TOTAL DEPTH: same	San Juan New Mexico
Same	14. API NO.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA	
	15. ELEVATIONS (SHOW DF, KDB, AND WD)
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	5176 GL
TEST WATER SHUT-OFF 🔲	
FRACTURE TREAT	
REPAIR WELL	(NOTE: Panet acculto of a utable and a state of a state
PULL OR ALTER CASING	(NOTE: Report results of multiple completion or zone change on Form 9–330.)
MULTIPLE COMPLETE	
CHANGE ZONES	
(other) Drilling X	
17 DECODINE PROPOSED OF COURTERS OFFICE OF A	
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state including estimated date of starting any proposed work. If well is di measured and true vertical depths for all markers and zones pertinent	rectionally drilled give subsurface locations and
See attached.	
bee accaenca.	
	• •
	10 10 10 10 10 10 10 10 10 10 10 10 10 1
ACUEPTED FO	A RECORD
MAR 10	
FARMINGTON D	4.
BY ***	DIST. 3
Subsurface Safety Valve: Manu. and Type	Set @ Ft.
	Set @ Ft.
18. I hereby certify that the foregoing is true and correct	
SIGNED TITLE Engineer	DATE <u>March 3, 1981</u>
(This space for Federal or State office	ce use)
APPROVED BY TITLE CONDITIONS OF APPROVAL, IF ANY:	DATE

MERRION & BAYLESS
NAVAJO G-5
990' FSL & 330' FEL
Section 30, T29N, R17W
San Juan County, New Mexico
14-20-603-5024

WELL HISTORY

- O2-27-81 Move in, rig up L & B Speed Drill. Spud 9-1/4" surface hole to 64 ft. Set 63 ft. of 7" 23 lbs/ft. surface @ 64 ft. w/ 12 sx class 'A' w/ 3% CACL₂. Circulated cement. WOCT. (SSD)
- 02-27-81 Drilled out from under surface w/ 6-1/4" bit and air. (SSD)
- 02-28-81 Drilling to 513 ft. w/ air. (SSD)
- O3-01-81 Mud up, drilled to 525 ft. G.L. Trip out. Trip in w/ core barrel. Cut 2-1/8" core from 525 ft. to 545 ft. Recovered 15 ft. of core. SDON. (SSD)
- O3-02-81 T.D. @ 600 ft. Trip out laying down drill pipe. Rig up Birdwell and ran Induction and Compensated Density logs. Ran 19 jts. of 4-1/2" K-55 casing to 599 ft. KB. Tally length 595.15 ft. PBTD 563 ft. Rig up Cementers Inc. and cemented w/ 85 sx Class 'B' w/ 1% CACL2. Circulated 3 bbls good cement to surface. Shut in. (SSD)